Artesia, NM 88216 5. LEASE

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES

	SL:	NM04473,	BHL:	NM02887-L
6.	IF IN	DIAN, ALLOTT	EE OR	TRIBE NAME

DEPARTMENT OF THE INTERIOR	SL: NM04473, BHL: NM02887-D
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GEOLOGICAL SORVET RECEIVED	Action of the same against the same of
THE REPORTS ON WELLS, IS	7. UNIT AGREEMENT NAME
SUNDRY NOTICES AND REPORTS ON WELLS	JAMES RANCH (fund
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME AUG 1 6 1988
RIR IN ARUM ARUM ARUM	UNIT land druck line
1. oil gas well other ROSWELL DISTRICT	9. WELL NO. O. C. D.
well — well	Q, C, D,
2. NAME OF OPERATOR	10. FIELD OR WILDCAT NAME
BELCO PETROLEUM CORPORATION	LOS MEDANOS MORROW-ATOKA
3. ADDRESS OF OPERATOR	11. SEC., T., R., M., OR BLK, AND SURVEY OR
411 PETROLEUM BUILDING MIDLAND, TX 79701	AREA SL: Sec 6, T-23-S, R-31-
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	BHL: Sec 7, T-23-S, R-31-
below.) AT SURFACE: 1980' FWL & 100' FSL, Sec 6	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	EDDY NEW MEXICO
AT TOTAL DEPTH: FNL & 1980' FWL, Sec 7	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	3001524420
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	3300 GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	(NOTE: Report results of multiple completion or zone
REPAIR WELL	change on Form 9-330.)
PULL OR ALTER CASING U MULTIPLE COMPLETE	
CHANGE ZONES	• -
ABANDON*	
(other) CASING REPORT	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta	ate all pertinent details, and give pertinent dates.
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly Stational Complete C	directionally drilled, give subsurface locations and
including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertino	ent to this work.)
71 00 Y 1 (13 1)	Top of liner - 11744' bottom
Ran 67 joints 5" 17.93#/ft. N-80 Hydrill lin	Nace H 6% Hallad 22 + 4% CFR2 +
of liner - 14640'. Cemented with 450 sacks C	111/183 O sacks to surface.
of liner - 14640'. Cemented With 450 Sacks C 3 sacks KCl. Plug down time: 8:53 AM MST, 7	/14/03. 0 Sacks to 55.2350
	• •

Subsurface Safety Valve: Manu. and Type		Set @	_ Ft.
18. I hereby certify that the foregoing is to SIGNED ROLL OF A Chair	rue and correct TITLEReceptionist	_ DATE	
	(This space for Federal or State office us	e)	
APPROVED BY	TITLE	DATE	

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

AUG 1 2 1983

ROSWELL NEW MEXICO