

MEASURED DEPTH FEET	DRIFT ANGLE D M	DRIFT DIRECTION D	COURSE LENGTH FEET	TRUE VERTICAL DEPTH FEET	RECTANGULAR COORDINATES FEET	DOSLEG SEVERITY DG/100FT
3500.	1 0	S 65 E	100.	3499.39	16.88 S 26.09 E	0.02
3600.	1 0	S 43 E	100.	3599.37	17.90 S 27.49 E	0.38
3700.	0 45	S 66 E	100.	3699.36	18.78 S 28.73 E	0.43
3800.	1 0	S 69 E	100.	3799.35	19.36 S 30.14 E	0.25
3900.	1 0	S 55 E	100.	3899.34	20.18 S 31.67 E	0.24
4000.	1 0	S 62 E	100.	3999.32	21.09 S 33.16 E	0.12
4100.	1 0	S 52 E	100.	4099.31	22.04 S 34.62 E	0.17
4200.	1 15	S 55 E	100.	4199.29	23.21 S 36.20 E	0.26
4300.	1 0	S 71 E	100.	4299.27	24.10 S 37.95 E	0.40
4400.	1 0	S 66 E	100.	4399.25	24.74 S 39.57 E	0.09
4500.	1 0	S 54 E	100.	4499.24	25.61 S 41.08 E	0.21
4600.	1 0	S 70 E	100.	4599.22	26.43 S 42.62 E	0.23
4700.	1 0	S 71 E	100.	4699.21	27.01 S 44.26 E	0.02
4800.	0 45	S 34 E	100.	4799.19	27.92 S 45.45 E	0.60
4900.	0 45	S 52 E	100.	4899.19	28.88 S 46.34 E	0.23
5000.	1 0	S 53 E	100.	4999.17	29.80 S 47.55 E	0.25
5100.	1 0	S 48 E	100.	5099.16	30.91 S 48.90 E	0.09
5200.	1 0	S 57 E	100.	5199.14	31.98 S 50.28 E	0.16
5300.	1 15	S 27 E	100.	5299.12	33.42 S 51.58 E	0.63
5348.	1 0	S 49 E	48.	5347.11	34.16 S 52.16 E	1.03
5440.	0 45	S 24 E	92.	5439.10	35.28 S 52.98 E	0.49
5500.	0 45	S 33 E	60.	5499.10	35.97 S 53.36 E	0.20
5600.	0 30	S 7 E	100.	5599.09	36.98 S 53.73 E	0.37
5700.	0 45	S 3 E	100.	5699.09	38.07 S 53.82 E	0.25
5800.	0 45	S 29 W	100.	5799.08	39.33 S 53.53 E	0.41
5900.	0 45	S 44 W	100.	5899.07	40.38 S 52.76 E	0.20
6000.	0 45	S 53 W	100.	5999.06	41.24 S 51.78 E	0.12
6100.	0 45	S 63 W	100.	6099.05	41.94 S 50.67 E	0.13
6200.	1 0	S 68 W	100.	6199.04	42.57 S 49.28 E	0.26
6300.	0 45	S 68 W	100.	6299.03	43.14 S 47.86 E	0.25