

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.G.S.	
LAND OFFICE	☒
OPERATOR	☒

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501
RECEIVED
APR 22 1983
O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL ☐ GAS ☒ WELL OTHER-	7. Unit Agreement Name
2. Name of Operator Pogo Producing Company ✓	8. Farm or Lease Name Lightfoot "Com"
3. Address of Operator P.O. Box 10340 Midland, Texas 79702	9. Well No. 1
4. Location of well UNIT LETTER J 1780 FEET FROM THE South LINE AND 2460 FEET FROM THE East LINE, SECTION 14 TOWNSHIP 24-S RANGE 28-E NMPM.	10. Field and Pool, or Wildcat Malaga Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 2977.2 GR	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4/16/83 TD 623'. Spud 26" hole 11:30 am CST 4/15/83. Drill 26" hole to 623'.
4/17/83 TD 623'. POH. Ran 14 jts 20" 94# K-55 ST&C Rg 3 csg. Attempt unsuccessfully to work csg through tight hole at 543'. POH 20" csg. Left 1 jt. 20" csg with shoe, float collar and two centralizers in hole. Ream hole with 26" bit.
4/18/83 TD 623'. Ream hole to top of fish at 579'. POH. Run tapered mill. Mill out float collar, POH. PU spear and jars and RIH.
4/19/83 TD 623'. Fish 1 jt 20" csg. RIH w/26" bit clean out to 623. Ran 16 jt 20" 94# K-55 ST&C Rg csg (623.03'), guide shoe 1.75', and float collar 2.5' (total string 627.28'). Guide shoe at 623' and float collar at 579'. Cmt w/1180 sx TLW w/1/4# celloseal/sx and 2% CaCl2 followed by 200 sx C1 C w/2% CaCl2. Circ 168 sx. CIP at 11:40 pm CST 4/18/83. WOC 6 1/4 hr.
4/20/83 TD 643'. WOC an additional 19 1/2 hr. (Total WOC 25 3/4 hr). Test csg to 1000 psi 30 min ok. Dr1 cmt and new formation.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED James R. Henry TITLE Division Engineer DATE 4/20/83
Original Signed By
Leslie A. Clements
APPROVED BY _____ TITLE Supervisor District II DATE APR 27 1983