

NM OIL CONS. COMMISSION
UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM-19842-A	
2. NAME OF OPERATOR Jake L. Hamon		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 611 Petroleum Building, Midland, Texas 79701		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FSL & 1980' FEL		8. FARM OR LEASE NAME Schalk Federal Com 33	
14. PERMIT NO.		9. WELL NO.	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3046' GR 3064.3' KB		10. FIELD AND POOL, OR WILDCAT Dublin Ranch-Atoka (Ext.) Dublin Ranch-Morrow (Ext.)	
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 33, T-22-S, R-28-E	
		12. COUNTY OR PARISH Eddy	
		13. STATE New Mexico	

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☒ **Spud & run surface casing**

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spudded 17-1/2" hole @ 5:00 P.M. 5-16-83.
2. Drilled 17-1/2" hole to 439' 5-17-83.
3. Set 13-3/8", 48#, 54.5#, 61# & 68#, H-40, J-55 & K-55, STC casing @ 437.83'. Cemented with 500 sx Class "C" cement + 2% CaCl 5-17-83. Circulated 96 sx cement to pits.
4. After waiting on cement 12 hours, nipples up 2 - 12" 3M BOPs and pressure tested casing to 900# for 1/2 hour with no pressure loss.
5. After 22 hours, started drilling 12-1/4" hole 5-19-83.

RECEIVED

MAY 31 1983

OIL & GAS

ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED *[Signature]*

TITLE Drilling Foreman

DATE 5-24-83

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

ACCEPTED FOR RECORD

JUL 13 1983

*See Instructions on Reverse Side

ROSWELL, NEW MEXICO