

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-19842-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Schalk Federal Com 33

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Dublin Ranch-Atoka (Ext.)
Dublin Ranch-Morrow (Ext.)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 33, T-22-S, R-28-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Jake L. Hamon

3. ADDRESS OF OPERATOR

611 Petroleum Building, Midland, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

660' FSL & 1980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3046' GR

3064.3' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Run Intermediate casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drilled 12-1/4" hole to 2,550' 5-22-83.
2. Set 9-5/8", 36# & 40#, J-55, K-55 & N-80, STC, LTC & Butt. casing at 2546.8' KB. Cemented with 900 sx Halliburton Light + 1/4# flocele/sx. Tailed in with 250 sx Class "H" Neat 5-23-83. Circulated 87 sx cement to pits.
3. After waiting on cement 18 hours, nipped up 11" 5M BOPs and pressure tested casing to 900# for 1/2 hour with no pressure loss 5-24-83.
4. Started drilling 8-3/4" hole 5-24-83.

RECEIVED

MAY 31 1983

OIL & GAS

ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

J. Hamon

TITLE

Drilling Foreman

DATE

5-24-83

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

RSP

JUL 14 1983

*See Instructions on Reverse Side

ROSWELL, NEW MEXICO