

UNITED STATES OF AMERICA  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR

Ammex Petroleum, Inc.

3. ADDRESS OF OPERATOR

Box 10507 Midland, TX 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FNL & 660' FWL Sec. 14

AT TOP PROD. INTERVAL: same

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☒

☐

☐

☐

☐

☐

☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

7/18/83 Rig Released 10:30 am MDT 7/17/83

7/20/83 Ran CBL from TD to 3000'. Cmt top @ 3670'

7/21/83 Tally 2 7/8" tbg. (5353') Spot 750 gal 7½% acetic acid. Prep to perf.

7/22/83 Perf w/2jspf 5312'-5318'. RIH w/tbg. Landed @ 5312' Swab 5 hrs. Rec. 59 BLW.

7/26/83 Acidize w/500 gal 7½% acid.

7/27/83 Swab 7 hrs. LD tbg. Prep to set plug & perf 3860'-3880'

7/28/83 Set CIBP @ 4200'. Perf 3860'-3880' w/2jspf. RIH w/tbg Land @ 3879'. Acidize w/500 gal 7½% acid. ISIP 300#, AIR 4.3 bpm.

7/29/83 Prep to swab.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*William E. Smith*

TITLE Engineer

DATE 8/1/83

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

AUG 1 5 1983