

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other Water Source Well

2. NAME OF OPERATOR
Amoco Production Company

3. ADDRESS OF OPERATOR
P. O. Box 68, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2160' FSL X 1960' FEL
AT TOP PROD. INTERVAL: (Unit J, NW/4, SE/4)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐ statud update

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in service unit 9-30-83. Ran 6-1/4" bit and tagged cement at 3000' and drilled to 3060'. Circulated hole clean. Perfed 2535'-37', 2542'-56', 2558'-63', 2565'-73', 2577'-81', 2589'-98', 2609'-15', 2618'-24', 2627'-36', 2727'-51', 2842'-50', 2916'-35', 2998'-3004' and 3030'-53' with a 4" casing gun and 2 SPF with 0° phasing. Ran packer and set at 2665'. Acidized with 2000 gals 7-1/2% LSTNE acid. Flushed to perfs with 31 bbl 2% KCL fresh water. Ran swab and recovered 79 BLW and 6 bbl of new water. Released packer and POH. Ran RBP with retrieving head, packer, and tubing. Set RBP at 2668' and packer set at 2447'. Pumped 1600 gals 7-1/2% LSTNE acid with additives. Flushed with 22 bbl 2% KCL water. Swabbed 6 hrs. and recovered apx. 61 BLW and 37 bbls of formation water. Released packer and dropped down and latch onto RBP and POH. Ran submersible pump in hole and began pump test. Pumped 66 BW in 1 hr and pump shut down. Currently shut-in evaluating additional work.

Subsurface Safety Valve: None and Type 1-F. J. Nash, HOU Rm 4.206 1-CMH Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Charles M. Terry TITLE Admin. Analyst DATE 10-13-83

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

ACCEPTED FOR RECORD

OCT 17 1983

007 211683
Form Approved.
Budget Bureau No. 47-R1424

5. LEASE
NM-0415688-A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Old Indian Draw Unit

9. WELL NO.
37

10. FIELD OR WILDCAT NAME
Indian Draw Delaware

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
18-22-28

12. COUNTY OR PARISH
Eddy

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KCL, LBS)
3084.1' GL

(NOTE: Report results of multiple completion or zone change on Form 9-331-C, 6 N. M.)

OCT 17 1983

ROSWELL, NEW MEXICO