

UNITED STATES
DEPARTMENT OF THE INTERIORSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

C/SF

BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ <i>Water Source.</i>		5. LEASE DESIGNATION AND SERIAL NO. NM-0415688-A	
2. NAME OF OPERATOR <i>Amoco Production Company</i>		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR <i>P.O. Box 68, Hobbs, NM 88240</i>		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface <i>2160' FSL X 1960' FEL, Section 18 (Unit J, NW/4, SE/4)</i>		8. FARM OR LEASE NAME <i>Old Indian Draw Unit</i>	
14. PERMIT NO.		9. WELL NO. <i>37</i>	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <i>3084.1' GL</i>		10. FIELD AND POOL, OR WILDCAT <i>Indian Draw Delaware</i>	
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <i>18-22-28</i>	
NOTICE OF INTENTION TO:		12. COUNTY OR PARISH <i>Eddy</i>	
SUBSEQUENT REPORT OF:		13. STATE <i>NM</i>	

TEST WATER SHUT-OFF ☐		PULL OR ALTER CASING ☐		WATER SHUT-OFF ☐		REPAIRING WELL ☐	
FRACTURE TREAT ☐		MULTIPLE COMPLETE ☐		FRACTURE TREATMENT ☐		ALTERING CASING ☐	
SHOOT OR ACIDIZE ☐		ABANDON* ☐		SHOOTING OR ACIDIZING ☐		ABANDONMENT* ☒	
REPAIR WELL ☐		CHANGE PLANS ☐		(Other) <i>squeeze plugs</i>			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MISU 9-15-84. RIH with retrievable bridge plug set at 3060' and pkd. out at 2976'. Acidized 2916' - 2935' with 500 gals 15% HCL. Grack 2842' - 3053' with 15,000 gals 2% KCL gel and sand. Cleaned out to 3060'. Set retrievable bridge plug at 2709' and cased with 10' sand. Set cmv retainer at 2450'. Pumped 300 sx class C treat. Reversed out 25 sx and drilled out to 2636'. Tested squeeze to 500 PSIX OK. Sub. Release retrievable bridge plug and ran tbg. Tbg. landed at 2478'. MOSU 9-28-84. Returned well to production.

045-BLM,C 1-JRB 1-FJN 1-BFC

I hereby certify that the foregoing is true and correct

SIGNED

Bonita Coble

TITLE

Administrative Analyst 10-12-84

(This space for Federal or State office use)

APPROVED BY

[Signature]

TITLE

AREA MANAGER
CARLSBAD REGION

DATE

*10-26-84*CONDITIONS OF APPROVAL IF ANY
OCT 17 1984

*See Instructions on Reverse Side