Form Approved. Budget Bureau No. 42-R1424

67			
ť.	1		1
	4	-	

UNITED STATES DEPARTMENT OF THE INTERIOR

PELANTMENT	OF THE HATELTION	10/01 11 72 6		
GEOLOG	ICAL SURVEY RECEIVED	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES A	ND REPORTS ON WELLS	7. UNIT AGREEMENT NAME		
	proposals.)	8. FARM OR LEASE NAME		
1. oil gas gas well o	ther	Bluewater - Federal		
		9. WELL NO.		
2. NAME OF OPERATOR		<u> </u>		
Mayne & Mertz, In	<u>C.</u>	10. FIELD OR WILDCAT NAME/		
3. ADDRESS OF OPERATOR		West Dark Canyon Delaware		
P. O. Box 183, Mi	dland. TX 79702	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
	RT LOCATION CLEARLY. See space 17	AREA		
below.)	The 2007 The Total Mark See Space 17	Sec. 18, T-23- 5 , R -26-E		
AT SURFACE: 1673'	FWL & 660' FSL of Sec.	12. COUNTY OR PARISH 13. STATE		
AT TOP PROD. INTERVAL:		1		
AT TOTAL DEPTH:		EddyNew Mexico		
		14. API NO.		
	TO INDICATE NATURE OF NOTICE,			
REPORT, OR OTHER DATA		15. ELEVATIONS (SHOW DF, KDB, AND WD)		
		KDB: 3424		
REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:	NOD: STET		
TEST WATER SHUT-OFF	And the state of	Well-district our district our state of the		
FRACTURE TREAT		ECENED 34		
SHOOT OR ACIDIZE				
REPAIR WELL		点《NOTE: Report results of multiple completion or zone		
PULL OR ALTER CASING		change on Form 9-330.)		
MULTIPLE COMPLETE				
CHANGE ZONES				
ABANDON*		RTESIA (FRICE)		
(other) <u>Casing & ceme</u>	nting Report	कुर्वमानिकिया वे प्रिकेश का Pass कुरावा <mark>- विशेष क्षाना कर के प्रकार के प्रक</mark>		
17. DESCRIBE PROPOSED OR (including estimated date of measured and true vertical of	COMPLETED OPERATIONS (Clearly stat starting any proposed work. If well is depths for all markers and zones pertiner	e all pertinent details, and give pertinent dates, irectionally drilled, give subsurface locations and it to this work.)*		
CASING:		1.55 / 070		
CASTING:	281' of 13-3/8" / 54.5# /	U-55 / SIC		
	Date set - 10/28/83			
CEMENTING:	Lead - 100 sks Halliburtor	n Lite		
	Tail - 400 sks Class "C" w/2% CaCl ₂			
		N/2% Cac12		
	Top of cement @ surface			
PRESSURE TEST:	1000 psi held 30 mins with	n no pressure drop.		
	•	. 1		
Subsurface Safety Valve: Manua	and Type Halliburton Insert	t Float Valve set @240 Ft.		
		v it indic trail to _ set (a)		
18. I hereby certify that the foreg	going is true and correct			
To late	enso Prist	DATE 11/12/84		
SIGNED	TITLE //ES/dur	DATE 11/12/84		

(This space for Federal or State office use)

APPROVED BY

DATE - - ACCOMPLET FOR THE CORD