

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

RECEIVED

JUN 14 1991

O. C. D.  
ARTESIA OFFICE

WELL API NO.

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Otis "34"

8. Well No.

1

9. Pool name or Wildcat

S. Carlsbad Morrow

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☐

GAS  
WELL ☒

OTHER

2. Name of Operator

Read & Stevens, Inc.

3. Address of Operator

P. O. Box 1518, Roswell, NM 88202

4. Well Location

Unit Letter F : 1828.5 Feet From The N Line and 1980 Feet From The W Line

Section 34

Township 22S

Range 27E

NMPM Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3107 GL

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Atoka recompletion attempt ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

In April of 1991, Read & Stevens, Inc. attempted a recompletion from the Wolfcamp to the Atoka formation. The existing Wolfcamp perms were squeezed with 125sx of cmt, and drilled out and tested to 1500 psi for 15 minutes successfully. The 5" liner was then cleaned out to a PBTD of 12,150'. After perforating the Atoka from 11002-11015', and acidizing with 1750 gal of 15% NEFe, the well tested noncommercial. A CIR was set at 10945', and the Atoka was squeezed with 50 sx cmt. Prep to evaluate the Morrow for recompletion.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Engineer

DATE June 11, 1991

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY  
MIKE WILLIAMS  
SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

JUN 18 1991

CONDITIONS OF APPROVAL, IF ANY: