

Form 9-331
(May 1963)

RECEIVED BY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NM OIL CONS. COMMISSION

Drawer DD

Artesia, NM 88210

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-19601

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Union 35 Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT
~~Dublin Ranch Atoka (Ext)~~
Dublin Ranch Morrow (Ext)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

35-22S-28E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Jake L. Hamon (Ph: 915-682-5218)

3. ADDRESS OF OPERATOR

611 Petroleum Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1780' FNL & 660' FWL of Section (SW/4 NW/4 - Unit E)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3064.1' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Well was spudded 11-30-83 by Abbot Bros. Rathold Machine.
2. Set 20' conductor casing at 40' GL on 12-1-83.
3. Started building road and location 12-2-83 and completed on 12-9-83.
4. Started moving in Hondo Drilling Company, Rig #12, 12-12-83.
5. Started drilling under conductor casing 12-16-83.
6. T.D. 17-1/2" hole 12-17-83.
7. Ran 11 joints (455.36') of 13-3/8", 48#, H-40, STC casing, set at 452' KB, cemented w/575 sx High Early 11 cement + 2% CaCl + 1/4# flocele/sx. Plug down at 11:30 A.M., 12-17-83 by Dowell.
8. After WOC 18 hours, NU 12" 3000# BOP, drilled cement and plug and pressure tested casing and casing seat w/600 psi for 30 minutes with no pressure loss.
9. Started drilling 12-1/4" hole 12-18-83.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drilling Foreman

DATE 12-21-83

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE

JAN 12 1984

*See Instructions on Reverse Side

ROSWELL, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.