| (Do not use this | GEOLOGICA | TATES SUBMIT I THE INTERIOR (Other ins (Other ins verse side) L SURVEY | 6. IF | Form approved. Budget Bureau No. 42-R1424. SE DESIGNATION AND SERIAL NO. RECEIVED BY |
|--|--|---|---|---|
| (Do not use this | IDRY NOTICES AND form for proposals to drill or Use "APPLICATION FOR PE | REPORTS ON WELLS | - · · · · · · · · · · · · · · · · · · · | INDIAN, ALLOTTEE OR TRIBE NAME |
| OIL GAS WELL WELL 2. NAME OF OPERATOR | | RM11- Ior such propesals.) | reservoir. | MAY 2 2 1984 |
| | X OTHER | | 7. UN | ARTESIA, OFFICE |
| Hamon Oil Co 3. ADDRESS OF OPERATO | | | | on 35 Federal |
| 4. LOCATION OF WELL (See also space 17 bel | Report location clearly and in ac | cordance with apy State requirement | bhit E) | ELD AND FOOL, OR WILLCAT LIN RANCH Atoka (Ext LIN RANCH Morrow (Ext C.T. R. M., OR BLK. AND SURVEY OR ABEA 22S-28E |
| 14. PERMIT NO. | 15. ELEVATION | NS (Show whether DF, RT, GR, etc.) 3064.1' GR | | dy New Mexico |
| 16. | Check Appropriate Bo NOTICE OF INTENTION TO: | ox To Indicate Nature of Notic | e, Report, or Other D SUBSEQUENT RE | • |
| nent to this work.) L. Ran Cement casing from | OFF PULL OR ALTER MULTIPLE COMP ABANDON* CHANGE PLANS OR COMPLETED OPERATIONS (Clean f well is directionally drilled, g)* Bond Log in 4-1/2" liner top to 3,200 | PLETE FRACTURE SHOOTING (Other) (No Com ly state all pertinent details, and gi rive subsurface locations and measur liner from 12,862' to | IUT-OFF TREATMENT X OR ACIDIZING X TE: Report results of mul pletion or Recompletion R re pertinent dates, includied and true vertical depth liner top at 10 | REFAIRING WELL ALTERING CASING ABANDONMENT* |
| Circulated 3. Circulated 4. POH with tu 5. Ran 3.75" O sion on wir 6. Ran Dress M 7. Ran Baker M 8. Tested in h 9. Reverse cir ure tested 0. Swabbed tub | mud out of hole wit hole w/10# brine pa bing 3-17-84. D Wireline Gauge Ri eline and set with [11] on tubing and d todel 8S-40 FB-1 Isc ole w/387 jts 2-7/8 culated w/410 bbls annulus to 500# for | the 10# bring d lamb 5 the 10# brine 3-16-84. top of packer at 12,7 bressed top of liner h top of packer and sea 3" OD 6.50# N-80 Vam T 10# Brine packer flui 1/2 hr. Installed u umberger perforated t te per ft. Total 20 ho | 00 gals acetic a aker Model D pac 03' 3-19-84. anger @ 10,923' 1 assembly and a &C tubing. d stung into pac pper tree assem hru tubing from | acid on bottom 3-17-84 cker w/mill out exten- 3-20-84. set in top of liner 3- cker @12,703'. Press- bly 3-23-84. |
| Swabbed tub 30 ball sea Rigged up C Halliburton and 34,500# | ing dry to 12,700'. lers on 3-26-84. RC Wireline and ran fraced w/48,000 ga 20/40 Mesh Interp | Halliburton acidize Radioactive Tracer S als Versagel 1500 cont cop with Radioactive m Frac and survey on 3- | d w/3000 gals 1 urvey on 3-29-8 aining 15% Meth aterial in inte | 4. anol and 25% CO ₂ , and |
| / | | 2 | | |
| 18. I hereby certify the SIGNED | at the foregoing is true and cor | TITLE Drilling FC | reman | DATE4-12-84 |
| (This spice for Fe | ACCEPTED TORRECO | RD | | DATE |
| CONDITIONS OF | APPROVAL, IF ANY : | | | |

-