

Form 3160-4
(July 1989)
(formerly 9-330)

RECEIVED

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONTACT RECEIVED
OFFICE FOR NUM
OF COPIES REQUIRED

(See other in-
structions on
reverse side)

BLM Roswell District
Modified Form No.
NM60-3160-3

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐
b. TYPE OF COMPLETION: NEW WELL ☐ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☒ DIFF. RESVR. ☐ Other ☐
2. NAME OF OPERATOR: BASS ENTERPRISES PRODUCTION CO.
3. ADDRESS OF OPERATOR: P.O. BOX 2760 MIDLAND, TEXAS 79702-2760
3a. Area Code & Phone No.: 806-583-2277

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*
At surface 660' FSL & 100' FWL SEC. 8, UNIT LETTER M
At top prod. interval reported below
At total depth 664' FSL & 1434' FEL, Sec. 7, UNIT LETTER O

9a. API Well No.: 30-015-24780
14. PERMIT NO.:
DATE ISSUED:

15. DATE SPUDDED: 4-10-84
16. DATE T.D. REACHED: 9-4-84
17. DATE COMPL. (Ready to prod.): 10-11-84
18. ELEVATIONS (DT, RKR, RT, GR, ETC.): GL 3311
19. ELEV. CASINGHEAD: 3311

20. TOTAL DEPTH, MD & TVD: MD- 13,500'
21. PLUG BACK T.D., MD & TVD: 14,450' MD
22. IF MULTIPLE COMPL., HOW MANY*: NO
23. INTERVAL DRILLED BY: X
24. PRODUCING INTERVAL(S) OF THIS COMPLETION - TOP, BOTTOM, NAME (MD AND TVD)*: 13,522' - 13,528MD - (13,210' - 13,216' TVD) - ATOKA

25. WAR DIRECTIONAL SURVEY MADE: YES
26. TYPE ELECTRIC AND OTHER LOGS RUN: NONE THIS COMPLETION
27. WAS WELL CORED: YES

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
20"	94#	610'	26"	700 SX LITE + 400 SX CL "C"	NONE
13 3/8"	54.5, 61, & 72#	4012'	17 1/2"	8150 SX LITE+400 SX CL "C"	NONE
7 5/8"	29.7, 33.7 & 39#	12265'	9 7/8"	734 SX LITE+400 SX CL "H"	NONE

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)
5"	11,811'	15,090	430	---

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2 3/8"	13,450'	13,450'

31. PERFORATION RECORD (Interval, size and number)

PERF. WITH 1 11/16" 00, PHASED ENERJET II CHARGES, 13,522' - 13,528' W/25 HOLES

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
13,522' - 13,528'	5,000 GALS. BLEND A-20.2 ACID WITH ADDITIVES, AND 10 1.3 SG RNCBS BALL SEALERS

33.* PRODUCTION

DATE FIRST PRODUCTION: 2-11-91
PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump): FLOWING
WELL STATUS (Producing or shut-in): PRODUCING

DATE OF TEST: 2-11-91
HOURS TESTED: 24
CHOKED SIZE: 14/64
PROD'N. FOR TEST PERIOD: 0
OIL—BBL.: 0
GAS—MCF.: 2206
WATER—BBL.: 62
GAS-OIL RATIO: -----

FLOW, TUBING PRESS.: 2250
CASING PRESSURE: PACKER
CALCULATED 24-HOUR RATE: 0
OIL—BBL.: 0
GAS—MCF.: 2206
WATER—BBL.: 62
OIL GRAVITY-API (CORR.): -----

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.): SOLD
TEST WITNESSED BY:

35. LIST OF ATTACHMENTS:

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED: R.C. HOUTCHENS, TITLE: SR. PRODUCTION CLERK, DATE: 3-11-91

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement or report.

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

38. GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Salado	1400	1461	Core #1 - Halite, Anhydrite	Delaware Bone Spring Wolfcamp Strawn Atoka	4034	4034
Salado	1461	1521	Core #2 - Halite, Anhydrite		7900	7900
Salado	1521	1554	Core #3 - Halite, Clay		11366	11174
Delaware	4034	7900	Sand, Lime, Shale		13082	12800
Bone Spring	7900	11366	Sand, Lime, Shale		13323	13030
Wolfcamp	11366	13082	Sand, Lime, Shale			
Strawn	13082	13323	Lime, Chert, Shale, Sand			
Atoka	13323	14378	Shale, Sand, Lime			