

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRI
(Other instructions
reverse side)

Budget Bureau No. 1004-0135 /25
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELL

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		JUN 25 1984		6. LEASE DESIGNATION AND SERIAL NO. LC 060613	
2. NAME OF OPERATOR MYCO Industries, Inc.		D. D. D ARTESIA, OFFICE		8. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 207 South 4th St., Artesia, NM 88210				7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 2310 FNL & 2310 FEL, Sec. 10-T22S-R28E				8. FARM OR LEASE NAME Hole in the Ground Federal	
				9. WELL NO. 1	
				10. FIELD AND FOOT, OR WILDCAT Undes. Delaware	
				11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA Unit G, Sec. 10-22S-28E	
14. PERMIT NO.		15. ELEVATIONS (Show whether DP, RT, CR, etc.) 3131' CR		12. COUNTY OR PARISH Eddy	
				13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	PLUG OR ALTER CASING
FRACTURE TREAT	SHUT IN COMPLETE
SHOOT OR ACIDIZE	ABANDON*
REPAIR WELL	CHANGE PLANS
(Other)	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREATMENT	ALTERING CASING
SHOOTING OR ACIDIZING	ABANDONMENT*
(Other)	

(Note: Report results of multiple completion on Well Completion or Re-completion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

6-15-84. Spudded 14-3/4" hole 4:45 PM 6-15-84.
6-16-84. Ran 13 joints of 10-3/4" 40.5# J-55 ST&C casing set 378'. 1-Texas Pattern notched guide shoe set 378'. Insert float set 357'. Cemented w/300 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 3:45 AM 6-16-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 48 sacks. WOC. Drilled out 5:15 PM 6-16-84. WOC 13 hours and 45 minutes. Cut off and welded on flow nipple. Tested casing to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Production Supervisor

DATE 6-19-84

This space for **ACCEPTED FOR RECORD**

APPROVED BY [Signature]
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JUN 27 1984

*See Instructions on Reverse Side

NEW MEXICO

Under U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.