

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SAN AFG	✓
FILE	✓
RECEIVED	
LAND OFFICE	✓
OPERATIONS	✓

OIL CONSERVATION REGISTRATION
P. O. BOX 1088
SANTA FE, NEW MEXICO 87504
OCT 11 1984

O. C. C.
ARTESIA OFFICE

Form O-103
Revised 10-1-77

5a. Indicate Type of Lease	
State ☐	Fee ☒
5. State Oil & Gas Lease No.	
30-015-24945	

SUNDY NOTICE AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSED PLUGS OR PLUG BACKS TO DIFFERENT RESERVOIR.
SEE REGISTRATION FOR PENALTY FOR FAILURE TO FILE FOR THIS PROVISION.)

1. OIL ☐ GAS ☒ OTHER ☐		7. Unit Agreement Date
2. Name of Operator Santa Fe Energy Company ✓		8. Name of Lease Name Burkham Fed Com
3. Address of Operator 500 W. Illinois, Midland, TX 79701		9. Well No. 1
4. Location of Well UNIT LETTER M 660 FEET FROM THE South LINE AND 990 FEET FROM THE West LINE, SECTION 12 TOWNSHIP 24S RANGE 28E NMPM.		10. Field and Pool, or Minorat Undes Malaga (Morrow)
11. Elevation (show whether DF, RT, GR, etc.) 2971.7 GL		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud date: 9-24-84 @ 12:15 PM MST

Casing: 9-27-84 20" 94#, K55 set @ 436'
Cmt w/300 sx Cl C 2% CaCl₂, 14.8 Slurry Weight. 70.6 BBL Slurry volume -
WOC 4 hrs. Run 1" tubing in hole to 318', dumped 4 yds gravel - cmt w/50
sx Cl C 4% CaCl₂. Tag cmt @ 260 - dumped 4 yds gravel - cmt w/50 sx Cl C
4% CaCl₂. WOC 2 1/2 hrs.

9-28-84 Pour 4 yds gravel - cmt w/100 sx Cl C 4% CaCl₂ WOC 2 3/4 hrs. Cmt top 175',
dumped 4 yds gravel & cmt w/100 sx Cl C, 4% CaCl₂. WOC 2 3/4 hrs. Cmt
top 122' - dumped 4 yds gravel & cmt w/100 sx Cl C, 2% CaCl₂. WOC 1 1/4 hrs.
Cmt top 66'. Dumped 4 yds gravel. Cmt w/200 sx - circ cmt to surface.
WOC 10 1/2 hrs. Test casing to 600psi.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Billie Hood TITLE Sr. Production Clerk DATE 10-5-84

APPROVED BY Original Signed By
Leslie A. Clements TITLE Supervisor District DATE OCT 9 1984
CONDITIONS OF APPROVAL, IF ANY: