STATE OF NEW MEXICO	
ERSY AND MINERALS DEPARTMENT C _ CONSERVATION DIVISIO	
	Ford C-103
RECEIVED BY O. BOX 2088 SANTA FE, NEV MEXICO 87501	Revised 10-1-78
TILE VIVI A TOTAL	
U.S.G.S. 1 1985	Sa. Indicate Type of Lease State Fee X
OFFHATOR IV	
ARTESIA, OFFICE API To. 30-015-24961	5. State Oil & Gas Lease No.
	XVIIII III III III III III III III III I
SUNDRY NOTICES AND REPORTS ON WELLS 100 HOT USE THIS FORM FOR PROPERSALS TO RELICION FOR COLUMN FLUG EACH PROPERSALS. IN THE FERMING OF THE COLUMN COLUMN FOR SUCH PROPERSALS.	
The state of the s	7. Unit Agreement Name
OIL X GAB OTHER	
ome of Operator	E. Fam or Lease Name
Phillips Petroleum Company	Drag C
ddress of Operatur	S. Well No.
Room 401, 4001 Penbrook Street, Odessa, Texas 79762	3
occijon of Well	<u> </u>
N 660 FEET FROM THE SOUTH LINE AND 1980 FEET FROM	South Carlsbad, Bone Spring
TEL PROM	
THE WEST LINE, SECTION 19 TOWNSHIP 23-S RANGE 27-E	
MAPE.	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3203'GR, 3219'RKB	Eddy ()
Check Appropriate Box To Indicate Nature of Notice, Report or Other	
· · · · · · · · · · · · · · · · · · ·	REPORT OF:
POUR REMEDIAL WORK	ALTERING CASING
APORABILY ABANDON COMMENCE DRILLING OPHS.	PLUE AND ABANDONMENT
L DE ALTER CABING CASING TEST AND CEMENT JOB X	PEGE AND APARSONMENT
OTHER	
0745.	
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including	estimated date of starting any proposed
work) SEE RULE 1103.	
Subsequent notice to report setting of 5-1/2" production casing.	
On 9-12-84, 5-1/2" 17#, K-55 ST&C casing was set at 5598'. Cemented w/1400 sx TLW w/	
10% DD, 10% salt, 1/4#/sx cellophane, 3#/sx gilsonite tailed w/450 sx C	
Displaced w/10 bbls 10% acetic acid and 199 bbls 2% KCL wtr, max psi 10	
plug w/1400 psi. Plug down @ 10:30 a.m. 9-12-84. Circ 250 sx cement. N casing & set 5-1/2" csg slips. Cm 10-15-84 loaded 5-1/2" casing w/2 bbl	
& pressured tested casing & BOF to 2000 psi held ok.	S OI 2% RCL WEF
a pressured tested casing a Bor to 2000 psi held ok.	
(TLW mixed at 11.8 ppg and 2.19 cf/sx. Class C mixed at 14.8 ppg and 1.	32 cf/sx)
•	
hereby certify that the information above is true and complete to the best of my knowledge and helief.	
to land	
Y Wii Just C. W. J. Mueller	March 28, 1985
TITLE TITLE	DATE

BY LARRY BROOKS GEOLOGIST - NMOCD