

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 30 days after the completion of any newly-drilled or deepened well. It shall be so completed by one of all electrical or radioactivity logs run on the well, and a summary of all special tests conducted, including drill stem tests. All depths mentioned shall be measured in depth. In the case of directionally drilled wells, true vertical depths shall also be reported. The multiple completion, from 1 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on some land, where only one copy is required. (Circular 1175)

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 2 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Greysburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Quize
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Elmore	T. Gr. Wash.	T. Morrison	T.
T. Toeb	T. Delaware Mountain Group 1915	T. Todilte	T.
T. Drifters	T. Delaware Sand 2035	T. Entrada	T.
T. Aba	T.	T. Wingate	T.
T. Wolfcamp	T. Cherry Canyon 2672	T. Chinle	T.
T. Penn.	T. Brushy Canyon 3795	T. Pennian	T.
T. Cisco (Bough C)	T. Bone Spring 5338	T. Penn. "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from	to	No. 4, from	to
No. 2, from	to	No. 5, from	to
No. 3, from	to	No. 6, from	to


IMPORTANT WATER SANDS

Indicate the rate of water inflow and elevation to which water rose in hole.

No. 1, from	to	feet
No. 2, from	to	feet
No. 3, from	to	feet
No. 4, from	to	feet


FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	2013	2013	Sand, rock				
2013	2238	225	Anhy				
2238	2640	402	Lime, sand, shale				
2640	3694	1054	Anhy, salt				
3694	5132	1438	Lime, shale, sand				
5132	5214	82	Lime, shale				
5214	5252	38	Shale				
5252	5600	348	Lime, shale				
	TD						



DRILLING COMPANY, INC.

P.O. Box 9680, Odessa, Texas 79767-9680
(915) 385-1130 (915) 563-4242



DATE: September 14, 1984
OPERATOR: Phillips Petroleum Company
P. O. Box 2130
Hobbs, New Mexico 88240
LEASE NAME AND WELL NUMBER: Drag-C 2 No. 3
LEGAL DESCRIPTION: Sec. 19, T-23-S, R-27-E
COUNTY AND STATE: Eddy County, New Mexico

MEASURED DEPTH	COURSE LENGTH	ANGLE OF INCLINATION	DISPLACEMENT PER 100 FEET	COURSE DISPLACEMENT	ACCUMULATIVE DISPLACEMENT
206	2.06	3/4	1.31	2.70	2.70
419	2.13	1 1/2	2.62	5.58	8.28
510	.91	2	3.49	3.18	11.46
593	.83	2 3/4	4.80	3.98	15.44
680	.87	3/4	1.31	1.14	16.58
931	2.51	1 1/2	2.62	6.58	23.16
1117	1.86	2	3.49	6.49	29.65
1260	1.43	1/4	.44	.63	30.28
1584	3.24	3	5.23	16.95	47.23
1707	1.23	3 1/2	6.10	7.50	54.73
1802	.95	3 1/4	5.67	5.39	60.12
1880	.78	2 1/4	3.93	3.07	63.19
2005	1.25	2 1/4	3.93	4.91	68.10
2160	1.55	2	3.49	5.41	73.51
2319	1.59	1 3/4	3.05	4.85	78.36
2500	1.81	1 1/4	2.18	3.95	82.31
2680	1.80	1	1.75	3.15	85.46
2881	2.01	1 1/4	2.18	4.38	89.84
3069	1.88	1 1/4	2.18	4.10	93.94

I declare under penalties prescribed in Article 6036c, R.S.C., that I am authorized to make this certification, that I have personal knowledge of the inclination data and facts placed on both sides of this form and that such data and facts are true, correct, and complete to the best of my knowledge.

Billy B. Griffin
Billy B. Griffin, Drilling Superintendent
RG Drilling Company, Inc.
(915) 385-1130

Subscribed and sworn before me this
20th day of Sept., 1984.

Kay Mangus
Kay Mangus - Notary Public
State of Texas
Commission Expires 3/17/88

MEASURED DEPTH	COURSE LENGTH	ANGLE OF INCLINATION	DISPLACEMENT PER 100 FEET	COURSE DISPLACEMENT	ACCUMULATIVE DISPLACEMENT
3370	3.01	1	1.75	5.27	99.21
3683	3.13	3/4	1.31	4.10	103.31
3995	3.12	1/2	.87	2.71	106.02
4300	3.05	1/2	.87	2.65	108.67
4615	3.15	3/4	1.31	4.13	112.80
4960	3.45	1	1.75	6.04	118.84
5252	3.48	1 1/4	2.18	6.37	125.21
5600	3.48	1 1/4	2.18	7.59	132.80