

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

RECEIVED BY

OCT 10 1984

O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5b. State Oil & Gas Lease No.	H 1525	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator HNG OIL COMPANY	8. Farm or Lease Name Lookout Crossing 36 State
3. Address of Operator P. O. Box 2267, Midland, Texas 79702	9. Well No. 1
4. Location of Well UNIT LETTER C 660 FEET FROM THE north LINE AND 1980 FEET FROM THE west LINE, SECTION 36 TOWNSHIP 23S RANGE 27E NMPM.	10. Field and Pool, or Wildcat Wildcat /Morrow/
15. Elevation (Show whether DF, RT, GR, etc.) 3123' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF: 9/26/84

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-25-84 - Set 2267 feet of 9-5/8" 36# K-55 ST&C

Cemented with 900 sacks Halliburton lite w/1/4#/sk flocele, mixed at 12.2 ppg.
Followed with 400 sacks Class C w/1/4#/sx. flocele & 2% CaCl, mixed at 14.8 ppg.

Circulated to surface. 30 minutes pressure tested to 2000#. WOC - 18 hours.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Betty Sildon
Betty Sildon

TITLE Regulatory Analyst

DATE 10/4/84

APPROVED BY Leslie A. Clements
Original Signed By
Supervisor District II

TITLE _____

DATE OCT 15 1984

CONDITIONS OF APPROVAL, IF ANY:

RECORDED

OCT -9 1984

U.S. DEPARTMENT OF JUSTICE
FEDERAL BUREAU OF INVESTIGATION
WASHINGTON, D.C. 20535
100-443888-100