

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN 33
(Other instructions
reverse side)

10-10-84

Form approved.
Budget Bureau No. 1004-0111
Expires August 31, 1985
5. LEASE DESIGNATION AND SERIAL NO.

LC 060613

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

ole in the Ground Federal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Undas. Delaware

11. SEC., T., R., M., OR B.E. AND
SUBJECT OR AREA

Unit H, Sec. 10-T22S-R28E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

2310 FNL & 990 REL, Sec. 10-22S-28E

14. DEPTH IN FEET (If less than 100 ft, show whether 10, 20, 30, etc.)

3135' GR

Check appropriate box to indicate nature of notice, hazard or other data

NOTICE OF INTEREST

REQUIREMENT REPORT OF

1. WATER SHUT-OFF

2. FLOODING

3. DRAINAGE

4. ESTAIRING WELL

5. FLOODING TREAT

6. FLOODING TREAT

7. FLOODING TREAT

8. ALTERING CANON

9. FLOODING TREAT

10. FLOODING TREAT

11. FLOODING TREAT

12. ALARMING TREAT

13. FLOODING TREAT

14. FLOODING TREAT

15. FLOODING TREAT

16. FLOODING TREAT

(Other) Production Log, Perforate, Tr. X

(NOTE: Report status of multiple completion on Well

Completion of well on Report and log form.)

17. GENERAL DESCRIPTION OF WORK (If work is to be done, show state of progress, details, and give estimated date of starting and completion of work. If work is already started, show subsurface locations and measured and vertical depths for all markers and other pertinent data.)

TD 6135'. Ran 149 jts 5-7/2" 15.5# J-55 casing set 6139'. 1-Regular guide shoe set 6139'. Float collar set 6087'. Cemented w/750 sacks Class "C" .6% CF-1, .2% AFS, 5#/sack salt. Compressive strength of cement - 650 psi in 24 hrs. PD 4:45 PM 10-25-84. Bumped plug to 1000 psi for 30 minutes, released pressure, float and casing held okay. WOC 18 hrs. WIH and perforated 5991-6004' w/10 .45" holes as follows: 5991, 92, 93, 94, 95, 6000, 01, 02, 03 and 04'. Acidized perforations 5991-6004' w/1500 gals 7 1/2% NEFE acid. Swab back well. Re-acidized perforations 5991-6004' w/1500 gals 7 1/2% NEFE acid and 10 ball sealers. Swabbed well, no oil or gas. WIH and perforated 5916-5939' w/10 .45" holes as follows: 5916, 17, 18, 29, 30, 31, 34, 35, 38 and 39'. Spent acid over perforations 5916-5939'.

18. I hereby certify that the foregoing is true and correct

SIGNED Guillermo A. Collett Title Production Supervisor

DATE 11-5-84

(This space for Federal or State use)

APPROVED BY [Signature]
CONDITIONS OF APPROVAL 0134

FILE

DATE

Collett

*See Instructions on Reverse Side