

MEASURED DEPTH FEET	DRIFT ANGLE D M	DRIFT DIRECTION D	COURSE LENGTH FEET	TRUE VERTICAL DEPTH FEET	R E C T A N G U L A R C O O R D I N A T E S FEET	DOGLEG SEVERITY DG/100FT
8851.	1 15	S 66 E	93.	8848.58	34.21 S	88.01 E
8944.	1 30	S 46 E	93.	8941.55	35.45 S	89.85 E
9038.	0 45	S 56 E	94.	9035.53	36.61 S	91.29 E
9131.	0 15	S 6 E	93.	9128.53	37.23 S	91.69 E
9225.	0 45	S 23 E	94.	9222.53	38.08 S	91.89 E
9318.	0 45	S 16 E	93.	9315.52	39.22 S	92.30 E
9412.	1 15	S 69 E	94.	9409.50	40.39 S	93.37 E
9505.	1 15	N 75 E	93.	9502.48	40.49 S	95.36 E
9598.	1 45	S 72 E	93.	9595.45	40.56 S	97.76 E
9692.	1 45	S 78 E	94.	9689.40	41.30 S	100.53 E
9785.	1 30	N 88 E	93.	9782.37	41.53 S	103.16 E
9879.	2 15	S 79 E	94.	9876.32	41.77 S	106.22 E
9972.	1 45	S 75 E	93.	9962.26	42.59 S	109.38 E
10065.	2 15	S 59 E	93.	10062.26	43.76 S	112.36 E
10159.	2 15	S 53 E	94.	10156.13	45.83 S	115.41 E
10252.	2 0	S 59 E	93.	10249.07	47.75 S	118.27 E
10346.	2 15	S 44 E	94.	10343.00	49.92 S	120.99 E
10439.	3 0	S 60 E	93.	10435.90	52.53 S	124.34 E
10532.	3 15	S 63 E	93.	10528.76	54.95 S	128.79 E
10626.	3 0	S 54 E	94.	10622.63	57.63 S	133.16 E
10719.	3 45	S 56 E	93.	10715.46	60.77 S	137.64 E
10813.	3 15	S 51 E	94.	10809.29	64.13 S	142.26 E
10906.	3 15	S 57 E	93.	10902.14	67.28 S	146.52 E
10999.	3 0	S 50 E	93.	10995.00	70.29 S	150.59 E
11093.	2 45	S 63 E	94.	11088.88	72.89 S	154.52 E
11186.	2 45	S 56 E	93.	11181.77	75.15 S	158.36 E
11280.	2 45	S 51 E	94.	11275.67	77.83 S	161.98 E
11373.	2 30	S 55 E	93.	11368.57	80.40 S	165.38 E
11467.	2 15	S 63 E	94.	11462.49	82.40 S	168.72 E
11560.	2 0	S 62 E	93.	11555.42	83.99 S	171.78 E