

MEASURED DEPTH FEET	DRIFT ANGLE D M	DRIFT DIRECTION D	COURSE LENGTH FEET	TRUE VERTICAL DEPTH FEET	R E C T A N G U L A R C O O R D I N A T E S FEET	DOGLEG SEVERITY DG/100FT
8925.	1 15	S 29 W	93.	8923.27	41.14 S	24.40 E 0.28
9018.	1 15	S 23 W	93.	9016.25	42.96 S	23.51 E 0.14
9112.	0 45	S 6 W	94.	9110.23	44.54 S	23.10 E 0.61
9205.	0 45	S 30 W	93.	9203.23	45.69 S	22.73 E 0.34
9298.	0 45	S 24 W	93.	9296.22	46.77 S	22.18 E 0.03
9392.	2 0	S 27 W	94.	9390.19	48.81 S	21.20 E 1.33
9485.	2 30	S 25 W	93.	9483.12	52.09 S	19.60 E 0.54
9578.	2 15	S 24 W	93.	9576.04	55.59 S	18.01 E 0.27
9671.	2 0	S 11 W	93.	9668.97	58.88 S	16.97 E 0.58
9764.	2 0	S 11 W	93.	9761.92	62.06 S	16.35 E 0.00
9857.	2 30	S 6 W	93.	9854.84	65.84 S	15.81 E 0.58
9951.	2 0	S 3 W	93.	9948.77	69.37 S	15.53 E 0.55
10044.	1 30	S 1 W	93.	10041.63	72.11 S	15.43 E 0.54
10137.	3 0	S 1 E	93.	10134.63	75.84 S	15.43 E 1.61
10230.	3 15	S 1 E	93.	10227.51	80.91 S	15.51 E 0.27
10323.	3 15	S 5 E	93.	10320.37	86.17 S	15.79 E 0.24
10416.	3 15	S 4 E	93.	10413.22	91.43 S	16.20 E 0.06
10509.	3 15	S 19 E	93.	10506.07	96.58 S	17.25 E 0.21
10603.	3 0	S 20 E	94.	10599.93	101.41 S	18.96 E 0.27
10696.	3 15	S 22 E	93.	10692.79	106.15 S	20.73 E 0.29
10789.	2 45	S 33 E	93.	10785.66	110.46 S	23.02 E 0.82
10882.	2 15	S 21 E	93.	10878.57	114.07 S	24.86 E 0.78
10975.	1 45	S 26 E	93.	10971.51	117.04 S	26.16 E 0.57
11068.	0 15	N 67 W	93.	11064.50	117.95 S	25.29 E 2.09
11162.	0 15	N 79 W	94.	11158.50	117.83 S	24.90 E 0.06
11255.	0 30	N 14 W	93.	11251.50	117.43 S	24.48 E 0.49
11348.	0 45	N 30 W	93.	11344.49	116.50 S	24.11 E 0.33
11441.	1 15	N 19 W	93.	11437.47	115.02 S	23.43 E 0.57
11534.	2 0	N 33 W	93.	11530.44	112.66 S	22.28 E 0.91
11627.	2 0	N 36 W	93.	11623.38	109.98 S	20.44 E 0.11

Eastman
Whipstock