

MEASURED DEPTH FEET	DRIFT ANGLE D M	DRIFT DIRECTION D	COURSE LENGTH FEET	TRUE VERTICAL DEPTH FEET	RECTANGULAR COORDINATES FEET	DIGLEG SEVERITY DG/100FT
3300.	0 15	S 26 E	93.	3299.00	11.98 S 57.38 E	0.04
3394.	0 15	N 1 E	94.	3393.00	11.92 S 57.67 E	0.52
3488.	0 30	N 82 E	94.	3487.00	11.50 S 58.05 E	0.56
3581.	0 15	S 44 W	93.	3579.99	11.91 S 58.26 E	0.77
3675.	0 15	S 52 E	94.	3673.99	12.27 S 58.28 E	0.40
3768.	0 30	N 76 E	93.	3766.99	12.40 S 58.86 E	0.43
3862.	0 30	N 74 E	94.	3860.99	12.18 S 59.65 E	0.02
3956.	0 30	S 74 E	94.	3954.98	12.18 S 60.46 E	0.22
4049.	0 30	S 49 E	93.	4047.98	12.57 S 61.17 E	0.23
4143.	0 15	S 86 W	94.	4141.98	13.03 S 61.01 E	0.74
4236.	0 15	S 44 W	93.	4234.98	13.11 S 60.66 E	0.19
4330.	0 15	S 25 E	93.	4328.98	13.51 S 60.59 E	0.30
4424.	0 30	S 11 E	93.	4422.97	14.11 S 60.73 E	0.31
4517.	0 15	S 11 W	93.	4515.97	14.78 S 60.68 E	0.28
4611.	0 15	S 1 W	94.	4609.97	15.18 S 60.63 E	0.05
4704.	0 30	S 29 W	93.	4702.97	15.77 S 60.48 E	0.33
4798.	0 0	0	94.	4796.97	16.13 S 60.28 E	0.53
4892.	0 45	S 32 W	94.	4890.97	16.65 S 59.95 E	0.80
4985.	0 45	S 50 W	93.	4983.96	17.56 S 59.16 E	0.25
5079.	0 30	S 34 W	94.	5077.95	18.32 S 58.47 E	0.32
5172.	0 15	S 37 W	93.	5170.95	18.82 S 58.12 E	0.27
5266.	0 15	N 36 W	94.	5264.95	18.82 S 57.77 E	0.43
5360.	0 30	S 52 W	94.	5358.95	18.74 S 57.22 E	0.60
5453.	0 30	S 33 W	93.	5451.94	19.33 S 56.67 E	0.18
5547.	0 30	S 24 W	94.	5545.94	20.05 S 56.28 E	0.08
5640.	0 45	S 8 E	93.	5638.94	21.05 S 56.14 E	0.45
5734.	0 30	S 37 W	94.	5732.93	22.01 S 55.89 E	0.57
5754.	0 45	S 2 E	20.	5752.93	22.22 S 55.83 E	2.40
5844.	0 30	S 8 W	90.	5842.92	23.19 S 55.78 E	0.30
5938.	0 30	S 9 W	94.	5936.92	24.01 S 55.66 E	0.01

Eastman
Whipstock