| ENERGY AND MINERALS DEPARTMENT | |
|--|--|
| DISTRIBUTION RECEIVED BY. O. BOX 2088 SANTA FE, NEW MEXIC | Form C-103 Revised 10-1-7 |
| DEC 28 1984 | \$a. Indicate Type of Lease |
| 0.8.0.3. | State Fee X |
| O. C. D. ARTESIA, OFFICE | 5, State Oil 6 Gas Lease No. |
| SUNDRY NOTICES AND REPORTS ON WELLS | |
| (DO NOT USE THIS FORW FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUC BACK TO'A DUST "APPLICATION FOR PERMIT -" (FORM C - 101) FOR SUCH PROPOSAL | 7, Unit Agreement Name |
| OTHER- | |
| 2. Name of Operator Pogo Producing Company | 6. Form or Leane Isame Lightfoot "Com" |
| P.O. Box 10340 Midland, Texas 7970 | 9, Well No. 2 |
| 4. Location of Well | 10. Field and Pool, or Wildcar |
| UNIT LETTER P 660 PEET PROM THE SOUTH LINE AN | 660 Malaga Morrow |
| THE East LINE, SECTION 14 TOWNSHIP 24-S BAN | ee 28-E |
| 15. Elevation (Show whether DF, RT, G GR 2978.5' | R, etc.) 12. County Eddy |
| Check Appropriate Box To Indicate Nature of NOTICE OF INTENTION TO: | Notice, Report or Other Data SUBSEQUENT REPORT OF: |
| PERFORM REMEDIAL WORK | WORK ALTERING CASING |
| TEMPORARILY ABANDON COMMENC | E DRILLING OPHS. |
| PULL OR ALTER CASINE CASING TO OTHER | EST AND CEMENT JOS X |
| OTHER | |
| 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and gi | ve pertinent dates, including estimated date of starting any proposed |
| 12/20/84 - RU Cactus Drilling Company Rig No. 1. Sp | |
| 12/20/84 - RU Cactus Drilling Company kig No. 1. 3P | Judded Well 6 7:00 pm (18) 22, 25, 211 |
| bit, Spud mud 8.8 ppg. Lost circ @ 82'. | Dry drill to 241. |
| bit, Spud mud 8.8 ppg. Lost circ @ 82'. 12/22/84 - TD 600'. Pumped pill w/LCM. Ran 15 jts + FS 1.12' (Total string 632.87'). Cents 1kd. FS @ 600', IF @ 557', Howco cemente | 631.75' 13 3/8" 61# K-55 ST&C Rg 3 casing s on 1, 3, & 5th jts. FS + 2 jts thrd ed w/200 sxs Lt + thickset + 1/4# flocele C + 2% CaCl + 1/4# flocele per sx (14.4 B4. Did not circulate. RIH weighted line, the annulus w/10 yds ready mix. Procedure |
| bit, Spud mud 8.8 ppg. Lost circ @ 82'. 12/22/84 - TD 600'. Pumped pill w/LCM. Ran 15 jts + FS 1.12' (Total string 632.87'). Cents lkd. FS @ 600', IF @ 557', Howco cemente per sx (12.7 ppg) followed w/600 sxs Cl C ppg). Bumped plug @ 12:45 pm MST 12/21/8 tagged cement @ 48' in annulus. Cemented approved by B.W. Weaver w/NMOCD. 16 1/4 H | 631.75' 13 3/8" 61# K-55 ST&C Ra 3 casina s on 1, 3, & 5th jts. FS + 2 jts thrd ed w/200 sxs Lt + thickset + 1/4# flocele C + 2% CaCl ₂ + 1/4# flocele per sx (14.4 ga. Did not circulate. RIH weighted line, d annulus w/10 yds ready mix. Procedure drs, WOC, cut off 13 3/8" csa, weld on |
| bit, Spud mud 8.8 ppg. Lost circ @ 82'. 12/22/84 - TD 600'. Pumped pill w/LCM. Ran 15 jts + FS 1.12' (Total string 632.87'). Cents lkd. FS @ 600', IF @ 557', Howco cemente per sx (12.7 ppg) followed w/600 sxs Cl C ppg). Bumped plug @ 12:45 pm MST 12/21/8 tagged cement @ 48' in annulus. Cemented approved by B.W. Weaver w/NMOCD. 16 1/4 Head & NU. 12/23/84 - TD 600'. 9.9# BW. 5 1/2 hrs. WOC, NU-& RI | Dry drill to 241. 631.75' 13 3/8" 61# K-55 ST&C Ro 3 casino s on 1, 3, & 5th jts. FS + 2 jts thrd ed w/200 sxs Lt + thickset + 1/4# flocele C + 2% CaCl ₂ + 1/4# flocele per sx (14.4 ga. Did not circulate. RIH weighted line, d annulus w/10 yds ready mix. Procedure drs, WOC, cut off 13 3/8" csa, weld on IH. Test BOP & csg to 1200# for 30 min, 0k/4" bit. |
| bit, Spud mud 8.8 ppg. Lost circ @ 82'. 12/22/84 - TD 600'. Pumped pill w/LCM. Ran 15 jts + FS 1.12' (Total string 632.87'). Cents lkd. FS @ 600', IF @ 557', Howco cemented per sx (12.7 ppg) followed w/600 sxs Cl Cppg). Bumped plug @ 12:45 pm MST 12/21/8 tagged cement @ 48' in annulus. Cemented approved by B.W. Weaver w/NMOCD. 16 1/4 head & NU. 12/23/84 - TD 600', 9.9# BW, 5 1/2 hrs. WOC, NU & RID Drill plug & cement and formation w/12 1/ | Dry drill to 241. 631.75' 13 3/8" 61# K-55 ST&C Ro 3 casino s on 1, 3, & 5th jts. FS + 2 jts thrd ed w/200 sxs Lt + thickset + 1/4# flocele C + 2% CaCl ₂ + 1/4# flocele per sx (14.4 ga. Did not circulate. RIH weighted line, d annulus w/10 yds ready mix. Procedure drs, WOC, cut off 13 3/8" csa, weld on IH. Test BOP & csg to 1200# for 30 min, 0k/4" bit. |
| bit, Spud mud 8.8 ppg. Lost circ @ 82'. 12/22/84 - TD 600'. Pumped pill w/LCM. Ran 15 jts + FS 1.12' (Total string 632.87'). Cents lkd. FS @ 600', IF @ 557', Howco cemented per sx (12.7 ppg) followed w/600 sxs Cl Cppg). Bumped plug @ 12:45 pm MST 12/21/8 tagged cement @ 48' in annulus. Cemented approved by B.W. Weaver w/NMOCD. 16 1/4 head & NU. 12/23/84 - TD 600', 9.9# BW, 5 1/2 hrs. WOC, NU & RID Drill plug & cement and formation w/12 1/ | 631.75' 13 3/8" 61# K-55 ST&C Rg 3 casing s on 1, 3, & 5th jts. FS + 2 jts thrd ed w/200 sxs Lt + thickset + 1/4# flocele C + 2% CaCl + 1/4# flocele per sx (14.4 ga. Did not circulate. RIH weighted line, d annulus w/10 yds ready mix. Procedure drs, WOC, cut off 13 3/8" csg, weld on IH. Test BOP & csg to 1200# for 30 min, Ok/4" bit. |