

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.O.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

RECEIVED BY
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501
FEB 11 1985
O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - I" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒

GAS WELL ☐

OTHER-

1. Name of Operator

Ray Westall

2. Address of Operator

P.O. Box 4 Loco Hills, NM 88255

3. Location of Well

UNIT LETTER E 660 FEET FROM THE West LINE AND 2200 FEET FROM
THE North LINE, SECTION 20 TOWNSHIP 23S RANGE 28E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Belco

9. Well No.

1

10. Field and Pool, or Wildcat

South Culebra Bluff

11. Elevation (Show whether DF, RT, GR, etc.)

3060. GR

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

FULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOB ☐

OTHER Spud, 8 5/8", T.D., 5 1/2" ☐

OTHER ☐

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-11-85 Spud 12 1/2" hole @ 10:45 A.M.

Ran 11 jts. STC, J-55, 24# 8 5/8" csg. Cemented @ 473' with 280 sxs
Class "C" 2% CaCl. Circulated 20 sxs to pit. Plug down @ 8:45 P.M.
W.O.C. 18 hr. press. 1000 psi 30 min., held.

1-12-85 Test BOP 800# 30 min. Held.

1-25-85 T.D. 6500'

1-26-85 Ran 6521' 17#, J-55 5 1/2" casing. Set @ 6500' with 1st stage: 575 sxs
C Poz, 5# salt, .3 of 1% Halad-4 & .2 of 1% CFR-2.
2nd stage: 1050 sxs Halliburton Lite, 1/4# flow seal. Tail in 150 sxs
C Poz, 5# salt. Circulated 125 sxs. Plug down @ 2:15 P.M. WOC 18 hr.

press. 1000 psi 30 min., held.

14. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ray Westall

TITLE Operator

DATE 2-8-85

APPROVED BY

TITLE

ORIGINAL SIGNED
BY LARRY BRUCE
GEOLOGIST - NMOC

DATE

FEB 18 1984

CONDITIONS OF APPROVAL, IF ANY: