

MEASURED DEPTH	DRIFT ANGLE D M	DRIFT DIRECTION D M	COURSE LENGTH	TRUE VERTICAL DEPTH	R E C T A N G U L A R C O O R D I N A T E S	DOGLEG SEVERITY
2786.00	1 0	S 12 O W	94.00	2779.89	60.16 S 130.04 E	0.31
2880.00	1 15	S 7 O W	94.00	2873.87	61.98 S 129.74 E	0.29
2974.00	1 0	S 9 O E	94.00	2967.85	63.82 S 129.77 E	0.42
3068.00	1 0	S 22 O W	94.00	3061.84	65.43 S 129.58 E	0.57
3162.00	1 0	S 10 O E	94.00	3155.82	67.04 S 129.42 E	0.59
3256.00	1 0	S 1 O W	94.00	3249.81	68.68 S 129.54 E	0.20
3350.00	1 0	S 1 O E	94.00	3343.79	70.32 S 129.54 E	0.04
3443.00	1 0	S 13 O W	93.00	3436.78	71.93 S 129.37 E	0.26
3537.00	1 30	S 4 O E	94.00	3530.76	73.97 S 129.21 E	0.66
3631.00	1 0	S 18 O E	94.00	3624.73	75.97 S 129.60 E	0.62
3725.00	1 15	S 9 O W	94.00	3718.72	77.80 S 129.81 E	0.54
3819.00	1 0	S 9 O E	94.00	3812.70	79.63 S 129.89 E	0.41
3913.00	1 15	S 9 O E	94.00	3906.68	81.42 S 130.35 E	0.32
4007.00	1 0	S 9 O W	94.00	4000.66	83.24 S 130.48 E	0.67
4100.00	0 45	S 68 O W	94.00	4094.65	85.61 S 130.71 E	0.71
4194.00	1 0	S 1 O E	94.00	4187.64	85.98 S 131.09 E	0.53
4288.00	1 0	S 42 O W	94.00	4281.63	87.48 S 130.53 E	0.78
4382.00	0 30	S 22 O W	94.00	4375.62	88.52 S 129.88 E	0.59
4476.00	1 0	S 31 O W	94.00	4469.61	89.62 S 129.33 E	0.54
4570.00	1 0	S 68 O W	94.00	4563.59	90.66 S 128.11 E	0.68
4664.00	0 45	S 17 O W	94.00	4657.58	91.69 S 127.17 E	0.84
4758.00	0 30	S 38 O W	94.00	4751.58	92.59 S 126.70 E	0.36
4851.00	0 45	S 81 O W	93.00	4844.57	93.09 S 125.85 E	0.55
4945.00	1 0	S 68 O W	94.00	4938.56	93.48 S 124.47 E	0.34
5039.00	0 45	S 48 O W	94.00	5032.55	94.23 S 123.26 E	0.42
5133.00	0 45	S 42 O W	94.00	5126.54	95.10 S 122.39 E	0.08
5227.00	0 30	S 36 O W	94.00	5220.54	95.90 S 121.74 E	0.27
5321.00	0 45	S 42 O W	94.00	5314.53	96.69 S 121.10 E	0.27
5415.00	1 0	S 38 O W	94.00	5408.52	97.79 S 120.18 E	0.27
5509.00	0 45	S 74 O W	94.00	5502.51	98.58 S 119.01 E	0.63

Eastman
Whipstock
A COMPANY