

MEASURED DEPTH	DRIFT ANGLE D M	DRIFT DIRECTION D M	COURSE LENGTH	TRUE VERTICAL DEPTH	R E C T A N G U L A R C O O R D I N A T E S	DOGLEG SEVERITY
242.00	0 0	N 0 0 E	0.00	242.00	0.00 N 0.00 E	0.00
304.00	1 15	S 45 0 E	62.00	304.00	0.48 S 0.48 E	2.02
397.00	2 45	S 64 0 E	93.00	396.94	2.35 S 3.11 E	1.74
490.00	3 30	S 63 0 E	93.00	489.80	4.62 S 7.65 E	0.81
583.00	4 30	S 63 0 E	93.00	582.57	7.56 S 13.43 E	1.06
676.00	5 45	S 65 0 E	93.00	675.20	11.20 S 20.89 E	1.36
769.00	6 15	S 66 0 E	93.00	767.69	15.23 S 29.74 E	0.55
862.00	6 15	S 68 0 E	93.00	860.13	19.19 S 39.06 E	0.23
955.00	5 45	S 75 0 E	93.00	952.62	22.27 S 48.27 E	0.95
1048.00	5 45	S 78 0 E	93.00	1045.16	24.45 S 57.33 E	0.32
1081.00	5 45	S 77 0 E	93.00	1077.99	25.19 S 60.55 E	0.61
1174.00	5 0	S 77 0 E	93.00	1170.00	27.30 S 69.00 E	0.81
1267.00	5 30	S 76 0 E	93.00	1263.19	36 S 77.26 E	0.54
1359.00	5 15	S 74 0 E	93.00	1354.88	38.80 S 85.52 E	0.58
1452.00	5 45	S 74 0 E	93.00	1448.88	41.78 S 93.92 E	0.55
1544.00	5 45	S 67 0 E	92.00	1538.89	38.16 S 102.50 E	0.33
1637.00	4 45	S 64 0 E	93.00	1631.50	41.69 S 110.24 E	1.11
1730.00	3 45	S 71 0 E	93.00	1724.25	44.32 S 116.60 E	1.21
1822.00	2 45	S 62 0 E	92.00	1816.10	46.40 S 121.38 E	1.22
1915.00	1 45	S 66 0 E	93.00	1909.02	48.00 S 124.66 E	1.09
1978.00	1 30	S 57 0 E	63.00	1972.00	48.85 S 126.23 E	0.57
2022.00	1 30	S 38 0 E	44.00	2015.98	49.63 S 127.08 E	1.13
2067.00	1 30	S 44 0 E	45.00	2060.97	50.51 S 127.85 E	0.35
2129.00	1 0	S 32 0 E	62.00	2122.95	51.58 S 128.68 E	0.91
2223.00	1 0	S 22 0 E	94.00	2216.94	53.04 S 129.42 E	0.19
2317.00	0 45	S 25 0 E	94.00	2310.93	54.35 S 130.00 E	0.27
2411.00	0 30	S 18 0 E	94.00	2404.92	55.31 S 130.37 E	0.28
2505.00	0 30	S 9 0 W	94.00	2498.92	56.12 S 130.43 E	0.25
2599.00	0 45	S 13 0 W	94.00	2592.91	57.12 S 130.24 E	0.27
2692.00	1 0	S 5 0 E	93.00	2685.90	58.53 S 130.14 E	0.40

Eastman Whipstock
AFTERMAN COMPANY