

RECEIVED BY

APR 10 1985

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYO. C. D.
ARTESIA OFFICE

SUNDY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other

2. NAME OF OPERATOR

Perry R. Bass

3. ADDRESS OF OPERATOR

P.O. Box 2760 Midland, Tx 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 800' FSL & 2300' FWL Unit Letter N

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) Spud Date & 8-5/8" CSG. ☒

5. LEASE

LC-069142A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Bass 10 Federal

9. WELL NO.

4

10. FIELD OR WILDCAT NAME

Indian Draw, East (Delaware)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 10 T22S, R28E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3110.2' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-30-85 Move in Rymes Drlg. Co.

Spud @ 12:00 Noon MST 3-30-85

DRLD. 12 1/4" hole to 410

Ran 9 Jts. 3 5/8" 24# K-55 ST&C Csq. set @ 410'

Cemented W/350 SK Class "C" cement + 1/4# SK Flocele

+2% CaCl₂ mixed @ 14.8 ppq, 1.32 yield. Bumped plug to 600 # @ 2:00A.M. MST² 3-31-85 Circulated 100 sk. float held. Witnessed by

Danny Cortez w/ BLM Carlsbad.

WOC & NU BOP equip. 12 hrs. Test BOP & Csq. to 1000# OK.

DRLG. 7-7/8" Hole 3-31-85.

Subsurface Safety Valve: Manu. and Type N/A Set @ 77 Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

R. Montchen

TITLE

Sr. Production Clerk

DATE

April 2, 1985

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD

APR 4 1985

*See Instructions on Reverse Side

CARLSBAD NEW MEXICO