ENERGY AND MINERALS DEPARTMENT	· •
DISTRIBUTION PECEIVED DE ATION DIV. ON	
TANTA SE TOTAL DIP O. BOX 2088	5a-m C 100
SANTA FE, NEW MEXICO 87501	Form C-103 - Revised 10-1.
U.s.o.s. APR -4 1985	To Journal D
LAND OFFICE	Sa. Indicate Type of Lease
OPERATOR V O. C. D.	State Fee X
ARTESIA, OFFICE	5. State Oil 6 Gus Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS	
TORN CALLES TO A DIFFERENT RESERVOIR.	
OIL SAS (	
WELL X OTHER.	7. Unit Agreement Name
12. Name of Operator	8. Farm or Lease liame
HNG OIL COMPANY  3. Address of Operator	Fort 18 Com.
	9. Weil No.
P. O. Box 2267, Midland, Texas 79702	1
1. Location of wall	10. Field and Pool, or Wildcat
WHIT LETTER E 1980 PEET FROM THE NORTH 895	Und. /Morrow/
LINE AND FEET FROM	The first own
THE West LINE. SECTION 18 TOWNSHIP 245 29E	
NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
2955.8' GR	Eddy
Check Appropriate Box To Indicate Nature of Notice, Report or Oth	VIIIIII
NOTICE OF INTENTION TO:	ner Data
SUBSEQUENT	REPORT OF:
PERFORM REMEDIAL WORK	•
TEMPORARILY ABANDON	ALTERING CASING
PULL OR ALTER CASING CHANGE PLANS	PLUG AND ABANDONMENT
AND CEMENT JOB	_
OTHER	
17. Describe Proposed of Complete Compl	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.	estimated date of starting and account
	, toward any proposed
3-24-85 - Set 600 foot of 12 2/04 car	
3-24-85 - Set 600 feet of 13-3/8" 61# K-55 ST&C. Cemented with 350 sack & 2% CaCl <sub>2</sub> mixed at 12.2 ppg., and 200 sacks Class H. 1/4# Pi	S HI. w/1//# R10001
& 2% CaCl <sub>2</sub> mixed at 12.2 ppg., and 200 sacks Class H - 1/4# F1 mixed at 14.7 ppg. Circulated 30 sacks to surface	ocele % 2% Caci
mixed at 14.7 ppg. Circulated 30 sacks to surface. 30 minute to 800 psi. WOC-19 hours.	S Dressure tookal
co ooo psi. woc-19 nours.	- Pressure tested
3-30-85 - Set 2610 feet of 0 5/04 20%	
3-30-85 - Set 2610 feet of 9-5/8" 36# K-55 ST&C. Cemented with 1200 sack & 2% CaCl <sub>2</sub> mixed at 12.2 ppg., and 350 sacks Class C. 1/4# Fri	ks HI. w/1//# Elecci-
& 2% CaCl <sub>2</sub> mixed at 12.2 ppg., and 350 sacks Class C - 1/4# Flomixed at 14.7 ppg. Circulated 100 sacks to surface 20	oceje % 2% Coci
mixed at 14.7 ppg. Circulated 100 sacks Class C - $1/4\#$ Florida to 1500 psi. WOC - 18 hours.	es pressure tostal
to 1500 psi. WOC - 18 hours.	os pressure tested
•	
· ·	
8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
to true and complete to the best of my knowledge and belief.	
ROLL CALL	•
Betty Gildon Regulatory Analyst	4/2/85
Original Signed By	DATE
Les A. Clements	
PHOLITIONS OF APPROVAL, IF ANY Supervisor District II	APR 5 1985