

## MARATHON OIL CO.

WELL DATA SHEET PRP, ED P &amp; A

CMT PLUG  
50' TO SURF

13 3/8" @ 450'

CMT PLUG  
400-500CMT PLUG  
1735-1835CMT PLUG  
2650-2550

8 5/8" @ 2600'

CALC TOC 2604

CIBP W/35' CMT  
CAP @ 3600'PERFED 3067-3075  
W/2JSPFPREFED 3637-3647  
W/2JSPF4 1/2" @ 3816  
CMT W/300SXCMT PLUG 3818-3918  
35 SX

CMT PLUG 4613-4502

TOP OF 4 1/2" @  
4563'

10 SK PLUG 5525-5425

10 SK PLUG 9010-8910

1 SK SAND ON TOP OF  
RBP

RBP @ 9650'

PERFS 9707-9857

PBD @ 9,950'

4 1/2" @ 10,650'

TD @ 10,700'

FIELD : EAST CARLSBAD (WOLFCAMP)

LEASE: DELTA FEE "B" # 1

LOCATION: UNIT B, 990' FNL &amp; 1980' FEL

SEC 14, TWP, 22S, RNG 27E

EDDY CO., NEW MEXICO

SPUDED 4/85

ELEVATION: 3082' GL 3110' KB

10,700' TD 9,950' PBD

SURFACE CASING: 13 3/8" 48#/FT, H-40 ST&amp;C

CMT W/450 SX. CIRC. 100 SX SET @ 450'

INTERMEDIATE CASING: 8 5/8" 24#/FT K-55 ST&amp;C

CMT/1830 SX. CIRC. 200 SX SET @ 2600'

PROD CSG SET 1-9-93

4 1/2" 11.6# @ 3816.25 KBM CMT WITH 300 SX

SQZD W/643 SX @ 9820', TOC 7500'  
 SQZD W/230 SX @ 7480' TOC 6550'  
 SQZD W/428 SX @ 6350' AND AGAIN W/ 50 SX.  
 SQZD AGAIN @ 7480' W/ 100 SX

MAKE SURE CMT IS 50' ABOVE AND BELOW  
 4 1/2" CSG STUB, 8 5/8" SHOE, 13 3/8"  
 SHOE

5 SX CMT 9631-9581

VOID SPACE TO BE FILLED WITH 10#  
 BRINE WITH 25# PER BbL GELL