

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN 1 PLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-060613

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back non-drilled reservoirs.
Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

BIG EDDY UNIT

8. FARM OR LEASE NAME

Big Eddy Unit Federal

9. WELL NO.

III

10. FIELD AND POOL, OR WILDCAT

East Indian Draw Delaware

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit A

Sec. 9 - T22S-R28E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

MYCO INDUSTRIES, INC.✓

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1140 FNL 330 FEL

Sec. 9-T22S-R28E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3136' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud 12 1/4" Hole 7 AM on August 17, 1985 with fresh water.
Drilled surface hole to 436' and ran 11 jts of 8 5/8" 24# to
436' with insert float at 398' and regular guide shoe at
463', cement with 275 sx cls "C" with 2% CACL plug down
at 7:30 PM on August 17, 1985.
Circulate 25 sx to pit, float held OK, WOC 18 hours
nipple up test BOP. Drill out with 7 7/8 bit.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE

8/19/85

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

AUG 20 1985

*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO