F (1999) (New Hold Streeg (Fig. 1997) (1997) (Fig. 1997) (1997)	DEPARTMENT OF THE INTE BUREAU OF LAND MANAGEME	RIODrawer DD NT Artesia, NM 88210	5. LEASE DESIGNATION LC065970-A	AI. 1985 6	
UN not use this for	Y NOTICES AND REPORTS to for proposals to drill or to deepen or plu se "APPLICATION FOR PERMIT" for suc	S ON WELLS	6. IF INDIAN, ALLOTTER	OR THIE NAVE	
I WELL XX WELL	OTHEE	No	7. UNIT AOLREMENT NA	71 E	
2. NAME OF OFFEATOR	8. FARM OR LEASE NAME				
The Eastland	Avalon Federal				
3. ADDREES OF OPERATOR	9. WELL NO.				
P.O.Drawer 3	1				
1 10:ATION OF WELL (Report location clearly and in accordance with any Store of the Store Store Store 17 below.) At surface			10. FILLD AND POOL, OF WILDCAT		
990' FNL and 990' FEL (NE/4NE/4)			11. SEC., T., R., M., OF ELE. AND SURVEY OF AREA		
			<u>Sec 7, T24S,</u>		
11 PELMIT NO.	15. ELEVATIONS (Show whethe		12. COUNTY OF FARIER		
30-015-25320	3000' GR, 3001'	DF ARTESIA, OFFICE	Eddy	New Mexico	
i.	Check Appropriate Box To Indicate	Nature of Notice, Report, or C)ther Data		
NOTICE OF INTENTION TO: BUBSEQ			CENT EXFORT OF :		
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATEL SHUT-OFF	EFFAIRING W		
FRACTURE TREAT	AEANDON ⁴	SEGOTING OR ACIDIZING	ALANDONMEN		
SHOGT ON ACIDIZE	CHANGE PLANS	(Other)	ALANDON ALA	-XX	
(Other)		(NOTE: Report results	: Report results of multiple completion on Well etion or Recompletion Report and Log form.)		
17. DESCEIDE PROPOSED OR Co- proposed work. If we nent to this work.) *	MPLETED GFERATIONS (Clearly state all perti- il is directionally drilled, give subsurface k	nent details, and give pertinent dates,	including estimated date	e of starting any	
	18, 1985, moved in and rig g. Ran CIBP on wireline a		csg. Dumped 35'		

2" EUE tubing. Ran CIBP on wireline and set @ 2750' in $4\frac{1}{2}$ " csg. Dumped 35 cement w/bailer to 2715'. Ran free point and shot $4\frac{1}{2}$ " csg @ 2370'. Laid down $4\frac{1}{2}$ " csg.

Ran 2" tbg to 2468' and circulated hole w/9.6# mud. Using Halliburton Services, set plug with 25 sx cement @ 2418'. Waited 16 hours and tagged cement plug @ 2313'. Set cement plug @ 351' w/60 sx cement. Waited 3 hours and tagged top of plug @ 270'. Set plug from 50' to surface with 15 sx. Installed 4½" X 4' marker. Plugging complete on November 19, 1985.

Casing left in hole: (a) 10-3/4", 40.5# surface csg set @ 295' and cement circulated w/200 sx. (b) $426' - 4\frac{1}{2}"$, 9.5#, J-55 csg from 2370' to 2796' and cemented with 60 sx.

Notification will be made as soon as rehabilitation of surface is complete.

18. I hereby certify that the foregoing is true and correct		·	
BIGNED George D. Nead on the	TITLE Vice President - Production	DATE _	11-25-85
(This space for rederal or State office use)	TITLE	DATE	4-16.86
APPROVED BY CONDITIONS OF APPROVAL, IF ANY :			

*See Instructions on Reverse Side