

RECEIVED BY

AUG 28 1985

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

O. C. SUNDRY NOTICES AND REPORTS ON WELLS

ARTESIAN OFFICE
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)1. oil well ☒ gas well ☐ other2. NAME OF OPERATOR
Perry R. Bass3. ADDRESS OF OPERATOR
P.O. Box 2760, Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 230' FSL & 1090' FEL Unit Letter P
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) Spud Date & Surface CSG ☒

SUBSEQUENT REPORT OF:

☐☐☐☐☐☐☐☐☒5. LEASE
LC - 060853 - A6. IF INDIAN, ALLOTTEE OR TRIBE NAME
-----7. UNIT AGREEMENT NAME
-----8. FARM OR LEASE NAME
Bass 3 Federal9. WELL NO.
110. FIELD OR WILDCAT NAME
Indian Draw East (Delaware)11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 3, T22S, R28E12. COUNTY OR PARISH
Eddy13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3142.7' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud @ 2:30 a.m. MDST 8-20-85.

Drld. 12 1/4" Hole to 257'.

Ran 6 jts. 8-5/8" 24# J-55 ST & C CSG. Float & Guide Shoe and 3 Centralizers set @ 257' Circ. CSG.

Cemented w/200 sx Class "C" Neat & 1/4#/sx Celloseal +2% CaCl₂ (14.8 ppg 1.32 ft. 3/sx) Displaced w/13.9 BFW Bump Plug to 700# @ 9:30 a.m. MDST, 8-20-85.

Circ. 45 sx to surface. WOC 11 1/2 hrs. Test BOP & Csg. to 1000# held O.K.

Drld. float collar, cement & shoe. Drlg. 7-7/8" hole 8-21-85.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

R.C. Hutchens

TITLE Sr. Prod. Clerk

DATE

August 23, 1985

(This space for Federal or State office use)

APPROVED BY

ACCEPTED FOR RECORD

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

AUG 27 1985

AUG 26 1985

*See Instructions on Reverse Side

CARISBAL NEW MEXICO