Commerly 9-331) DEPAR	RTMENT OF THE LATE	CONS. SCOMIT IN TRANCE ERIOR verse alder	Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO. NM-0426782
SUNDRY NO (Do not use this form for produce "APPI	OTICES AND REPORTS openals to drill or to deepen or pl LICATION FOR PERMIT—" for su	S ON WELLS us back to a different reservoir.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GIL GAS WELL X OTHER 2. NAME OF OPERATOR EXXON Corporation 3. ADDRESS OF OPERATOR		RECEIVED BY	7. UNIT AGREEMENT NAME
		001 15 1985	8. PARM OR LEASE NAME Mary Federal
P. O. Box 1600, Midl. 4. LOCATION OF WELL (Report location See also space 17 below.) At surface	and, TX 79702 D clearly and in accordance with	O. C. D.	9. WELL NO. 5 10. FIELD AND POOL, OR WILDOAT Undesig. Sheep Draw-Morre
709'FSL & 1829' FWL (of Sec. (SE SW)		Ga Survey or AREA Sec. 11-T23S-R25E
14. PERMIT NO.	16. ELEVATIONS (Show whether	DF, RT, GR, etc.)	12. COUNTY OF PARISE 13. STATE Eddy NM
Check A	Appropriate Box To Indicate	Nature of Notice, Report, o	or Other Data
TEST WATER SHUT-OFF			SEQUENT ESPORT OF:
FRACTURE TREAT	NULTIPLE COMPLETE	WATER SHUT-OFF FRACTURE TREATMENT	REPAIRING WELL
EHOUT OR ACIDIZE	ABANDON*	BHOOTING OR ACIDIZING	ALTEBING CABING ABANDONMENT®
(Other)	CHANGE PLANS	(Other)	Casing Report X ults of multiple completion on Well completion Report and Log form.)
0.2/.05			napletion Report and Log form.) tes, including estimated date of starting any rical depths for all markers and gones perti-
Repaired leaks on ki psi. Had to repair	Lite. Circulate to 11 lines, spools & ch leaks before testing ineering office. TO	: 1613'. Circulated of surface. Pack off cs oke manifold. Tested to 1500 psi-OK. Test C-1556'. Waited to	csg. Comented w/400 g. w/38" pea gravel. csg. & BOP's to 200
Repaired leaks on ki psi. Had to repair O'Hare w/State Engi	Lite. Circulate to 11 lines, spools & ch leaks before testing ineering office. TO	surface. Pack off cs oke manifold. Tested	esg. Comented w/400 g. w/38" pea gravel. csg. & BOP's to 200 witnessed by Keith tal of 56 hours on
Repaired leaks on ki psi. Had to repair O'Hare w/State Engi	Lite. Circulate to 11 lines, spools & ch leaks before testing ineering office. TO	surface. Pack off cs oke manifold. Tested	csg. Comented w/400 g. w/38" pea gravel. csg. & BOP's to 200
Repaired leaks on ki psi. Had to repair O'Hare w/State Engi cement before drill	Lite. Circulate to 11 lines, spools & ch leaks before testing ineering office. TO ing.	surface. Pack off cs oke manifold. Tested	esg. Comented w/400 g. w/38" pea gravel. csg. & BOP's to 200 witnessed by Keith tal of 56 hours on
Repaired leaks on ki psi. Had to repair O'Hare w/State Engi cement before drill I hereby certify that the foregoing is signed	Lite. Circulate to 11 lines, spools & ch leaks before testing incering office. To ing.	surface. Pack off cs oke manifold. Tested	esg. Comented w/400 g. w/38" pea gravel. csg. & BOP's to 200 witnessed by Keith tal of 56 hours on
Repaired leaks on kingsi. Had to repair O'Hare w/State Enging cement before drill I hereby certify that the foregoing in the space for Federal or State office. (This space for Federal or State office.)	Lite. Circulate to 11 lines, spools & ch leaks before testing incering office. To ing.	surface. Pack off cs surface. Pack off cs oke manifold. Tested to 1500 psi-OK. Test C-1556'. Waited to	esg. Comented w/400 g. w/38" pea gravel. csg. & BOP's to 200 witnessed by Keith tal of 56 hours on
Repaired leaks on kingsi. Had to repair O'Hare w/State Enging cement before drill I hereby certify that the foregoing in the space for Federal or State off ACCOPTED	s true and correct TITLE TITLE TITLE TO RECORD	surface. Pack off cs surface. Pack off cs oke manifold. Tested to 1500 psi-OK. Test C-1556'. Waited to	esg. Cemented w/400 g. w/38" pea gravel. csg. & BOP's to 200 witnessed by Keith tal of 56 hours on
Repaired leaks on ki psi. Had to repair O'Hare w/State Engi cement before drill I hereby certify that the foregoing is SIGNED / COUPTED APPROVED BY ACCUPTED CONDITIONS OF APPROVAL, IF	s true and correct TITLE TITLE TITLE TO RECORD	surface. Pack off cs surface. Pack off cs oke manifold. Tested to 1500 psi-OK. Test C-1556'. Waited to	csg. Cemented w/400 g. w/38" pea gravel. csg. & BOP's to 200 witnessed by Keith tal of 56 hours on

*See Instructions on Reverse Side