| Form 3160-5 November 1983) Formerly 9-331) DEP | UN ^{ET} ED STATES ARTML & OF THE IN | ITERIOR verse alde | CATE* DD re- 5. LEASE DESIGNATION AND SERIAL NO |
|--|--|--|--|
| В | UREAU OF LAND MANAG | EMENI 88210 | NM 59386 |
| SUNDRY (Do not use this form for Use "A | NOTICES AND REPO proposals to drill or to deepen o PPLICATION FOR PERMIT-" to | | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME T. |
| | CH ER | RECEIVED BY | 7. UNIT AGREEMENT NAME |
| NAME OF OPERATOR | / | | 8. FARM OR LEASE NAME |
| HNG OIL COMPANY 🗸 | | APR 17 1986 | Owen Mesa 25 Fed. Com. |
| ADDRESS OF OPERATOR | | | 8. WELL NO. |
| | idland, Texas 79702 ation clearly and in accordance w | O. C. D. | 1 |
| See also space 17 below.) At surface | actor cleany and la accordance w | in any state requirements." | 10 FIELD AND POOL, OR WILDCAT |
| | 7.11 1.1 | | WOwen Mesa /Morrow/ |
| 1980' FSL & 760' | гмГ | | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA |
| PERMIT NO. | 15. ELEVATIONS (Show wh | ether DF BT GR etc.) | Sec. 25, T24S, R29E 12. COUNTY OF PARISH 13. STATE |
| | 3080.0' | | |
| | 1 3080.0 | GA | Eddy NM |
| Che | ck Appropriate Box To Indi | cate Nature of Notice, Repo | or Other Data |
| | | | |
| NOTICE O | F INTENTION TO : | _ | SUBSEQUENT REPORT OF: 3/31/86 |
| TEST WATER SHUT-OFF | PCLL OR ALTER CASING | WATER SHUT-OFF | BEPAIRING WELL |
| FRACTURE TREAT | MULTIPLE COMPLETE | FRACTUBE TREATMEN | |
| FRACIORE IREAL | ABANDON* | - | |
| SHOOT OR ACIDIZE | | SHOOTING OR ACIDIZ | |
| | CHANGE PLANS | - SHOOTING OR ACIDIZ | |
| SHOOT OR ACIDIZE REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLET proposed work. If well is nent to this work.)* | CHANGE PLANS TED OPERATIONS (Clearly state all J directionally drilled, give subsurfa feet of 9-5/8" K-55 | L-80 40#. | t results of multiple completion on Well Recompletion Report and Log form.) at dates, including estimated date of starting any revertical depths for all markers and zones perti- |
| SHOOT OR ACIDIZE REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLET proposed work. If well is nent to this work.)* 4-3-86 - Set 3200 Cemented Followed Did not o | CHANGE PLANS TED OPERATIONS (Clearly state all p directionally drilled, give subsurfa feet of 9-5/8" K-55 with 450 sacks HL w, with 400 sacks Class circulated. Ran 630 | L-80 40#. /½# Flocele & 2% CaCl s C w/½# Flocele & 2% CaCl | 2 test & cement job t results of multiple completion on Well Recompletion Report and Log form.) at dates, including estimated date of starting any revertical depths for all markers and zones perti- 2 mixed at 12.7 ppg. 5 CaCl ₂ mixed at 14.8 ppg. cemented with 200 sacks |
| SHOOT OR ACIDIZE REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLET proposed work. If well is nent to this work.)* 4-3-86 - Set 3200 Cemented Followed Did not of Class C n | CHANGE PLANS FED OPERATIONS (Clearly state all J directionally drilled, give subsurfa feet of 9-5/8" K-55 with 450 sacks HL w, with 400 sacks Class circulated. Ran 630 nixed at 14.8 ppg. | L-80 40#. | 2 test & cement job t results of multiple completion on Well Recompletion Report and Log form.) at dates, including estimated date of starting any revertical depths for all markers and gones perti- 2 mixed at 12.7 ppg. CaCl ₂ mixed at 14.8 ppg. cemented with 200 sacks to surface. |
| SHOOT OR ACIDIZE REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLET proposed work. If well is nent to this work.)* 4-3-86 - Set 3200 Cemented Followed Did not of Class C n | CHANGE PLANS FED OPERATIONS (Clearly state all J directionally drilled, give subsurfa feet of 9-5/8" K-55 with 450 sacks HL w, with 400 sacks Class circulated. Ran 630 nixed at 14.8 ppg. | (Other) Casing (Norr: Report Completion or Pertinent details, and give pertiner ice locations and measured and tru L-80 40#. /½# Flocele & 2% CaCl s C w/½# Flocele & 2% feet of 1" pipe and Circulated 25 sacks t | 2 test & cement job t results of multiple completion on Well Recompletion Report and Log form.) at dates, including estimated date of starting any revertical depths for all markers and gones perti- 2 mixed at 12.7 ppg. CaCl ₂ mixed at 14.8 ppg. cemented with 200 sacks to surface. |
| SHOOT OR ACIDIZE REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLET proposed work. If well is nent to this work.)* 4-3-86 - Set 3200 Cemented Followed Did not of Class C n | CHANGE PLANS TED OPERATIONS (Clearly state all p directionally drilled, give subsurfa feet of 9-5/8" K-55 with 450 sacks HL w with 400 sacks Class circulated. Ran 630 mixed at 14.8 ppg. (| L-80 40#. /½# Flocele & 2% CaCl s C w/½# Flocele & 2% CaCl feet of 1" pipe and Circulated 25 sacks t b 2000#. WOC - 24-1/ | 2 test & cement job t results of multiple completion on Well Recompletion Report and Log form.) at dates, including estimated date of starting any revertical depths for all markers and gones perti- 2 mixed at 12.7 ppg. CaCl ₂ mixed at 14.8 ppg. cemented with 200 sacks to surface. |
| SHOOT OR ACIDIZE REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLET proposed work. If well is nent to this work.)* 4-3-86 - Set 3200 Cemented Followed Did not of Class C n | CHANGE PLANS FED OPERATIONS (Clearly state all J directionally drilled, give subsurfa feet of 9-5/8" K-55 with 450 sacks HL w, with 400 sacks Class circulated. Ran 630 nixed at 14.8 ppg. | L-80 40#. /½# Flocele & 2% CaCl s C w/½# Flocele & 2% CaCl feet of 1" pipe and Circulated 25 sacks t b 2000#. WOC - 24-1/ | 2 test & cement job t results of multiple completion on Well Recompletion Report and Log form.) at dates, including estimated date of starting any revertical depths for all markers and gones perti- 2 mixed at 12.7 ppg. CaCl ₂ mixed at 14.8 ppg. cemented with 200 sacks to surface. |
| SHOOT OR ACIDIZE REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLET proposed work. If well is nent to this work.)* 4-3-86 - Set 3200 Cemented Followed Did not of Class C n | CHANGE PLANS TED OPERATIONS (Clearly state all p directionally drilled, give subsurfa feet of 9-5/8" K-55 with 450 sacks HL w with 400 sacks Class circulated. Ran 630 mixed at 14.8 ppg. (| L-80 40#. /½# Flocele & 2% CaCl s C w/½# Flocele & 2% CaCl feet of 1" pipe and Circulated 25 sacks t b 2000#. WOC - 24-1/ | 2 test & cement job t results of multiple completion on Well Recompletion Report and Log form.) at dates, including estimated date of starting any revertical depths for all markers and gones perti- 2 mixed at 12.7 ppg. CaCl ₂ mixed at 14.8 ppg. cemented with 200 sacks to surface. |
| SHOOT OR ACIDIZE REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLET proposed work. If well is nent to this work.)* 4-3-86 - Set 3200 Cemented Followed Did not of Class C n | CHANGE PLANS TED OPERATIONS (Clearly state all p directionally drilled, give subsurfa feet of 9-5/8" K-55 with 450 sacks HL w with 400 sacks Class circulated. Ran 630 mixed at 14.8 ppg. (| (Other) Casing (Nors: Report Completion or Pertiment details, and give pertimer ice locations and measured and tru L-80 40#. /½# Flocele & 2% CaCl s C w/½# Flocele & 2% feet of 1" pipe and Circulated 25 sacks t to 2000#. WOC - 24-1/ | 2 test & cement job t results of multiple completion on Well Recompletion Report and Log form.) and dates, including estimated date of starting any revertical depths for all markers and gones perti- 2 mixed at 12.7 ppg. 4 CaCl ₂ mixed at 14.8 ppg. cemented with 200 sacks to surface. 2 hours. |
| SHOOT OR ACIDIZE REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLET proposed work. If well is nent to this work.)* 4-3-86 - Set 3200 Cemented Followed Did not of Class C n | CHANGE PLANS TED OPERATIONS (Clearly state all) directionally drilled, give subsurfa feet of 9-5/8" K-55 with 450 sacks HL w, with 400 sacks Class circulated. Ran 630 mixed at 14.8 ppg. (Clearly state all) es pressure tested to ACCEPTED FOR ADR 14 19 | (Other) Casing (Norr: Report Completion or Pertiment details, and give pertimer ice locations and measured and tru L-80 40#. /¼# Flocele & 2% CaCl s C w/¼# Flocele & 2% feet of 1" pipe and Circulated 25 sacks t to 2000#. WOC - 24-1/ RECORD | 2 test & cement job t results of multiple completion on Well Recompletion Report and Log form.) at dates, including estimated date of starting any revertical depths for all markers and gones perti- 2 mixed at 12.7 ppg. CaCl ₂ mixed at 14.8 ppg. cemented with 200 sacks to surface. |
| SHOOT OR ACIDIZE REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLET proposed work. If well is nent to this work.)* 4-3-86 - Set 3200 Cemented Followed Did not of Class C n | CHANGE PLANS FED OPERATIONS (Clearly state all p directionally drilled, give subsurfa feet of 9-5/8" K-55 with 450 sacks HL w with 400 sacks Class circulated. Ran 630 mixed at 14.8 ppg. (Des pressure tested to ACCEPTED FOR AMO | (Other) Casing (Norr: Report Completion or Pertiment details, and give pertimer ice locations and measured and tru L-80 40#. /¼# Flocele & 2% CaCl s C w/¼# Flocele & 2% feet of 1" pipe and Circulated 25 sacks t to 2000#. WOC - 24-1/ RECORD | 2 test & cement job t results of multiple completion on Well Recompletion Report and Log form.) and dates, including estimated date of starting any revertical depths for all markers and gones perti- 2 mixed at 12.7 ppg. 4 CaCl ₂ mixed at 14.8 ppg. cemented with 200 sacks to surface. 2 hours. |
| SHOOT OR ACIDIZE REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLE proposed work. If well is nent to this work.)* 4-3-86 - Set 3200 Cemented Followed Did not of Chass C m 30 minute | CHANGE PLANS TED OPERATIONS (Clearly state all f directionally drilled, give subsurfa feet of 9-5/8" K-55 with 450 sacks HL w, with 400 sacks Class circulated. Ran 630 mixed at 14.8 ppg. (C ACCEPTED FOR ACCEPTED FOR ADD APR 14 19 CARISBAD, NEW | (Other) Casing (Norr: Report Completion or Pertiment details, and give pertimer ice locations and measured and tru L-80 40#. /¼# Flocele & 2% CaCl s C w/¼# Flocele & 2% feet of 1" pipe and Circulated 25 sacks t to 2000#. WOC - 24-1/ RECORD | 2 test & cement job t results of multiple completion on Well Recompletion Report and Log form.) and dates, including estimated date of starting any revertical depths for all markers and gones perti- 2 mixed at 12.7 ppg. 4 CaCl ₂ mixed at 14.8 ppg. cemented with 200 sacks to surface. 2 hours. |
| SHOOT OR ACIDIZE REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLET proposed work. If well is nent to this work.)* 4-3-86 - Set 3200 Cemented Followed Did not Chass C n 30 minute 1 hereby certify that the foreg SIGNED | CHANGE PLANE FED OPERATIONS (Clearly state all I directionally drilled, give subsurfa feet of 9-5/8" K-55 with 450 sacks HL w, with 400 sacks Class circulated. Ran 630 nixed at 14.8 ppg. (C ES pressure tested to ACCEPTED FOR ACCEPTED FOR ADR 14 19 CARISBAD, NEW | (Other) Casing (Nors: Report Completion or Pertinent details, and give pertiner ice locations and measured and tru L-80 40#. /½# Flocele & 2% CaCl s C w/½# Flocele & 2% feet of 1" pipe and Circulated 25 sacks t D 2000#. WOC - 24-1/ RECORD | 2 test & cement job t results of multiple completion on Well Recompletion Report and Log form.) and dates, including estimated date of starting any revertical depths for all markers and gones perti- 2 mixed at 12.7 ppg. 3 CaCl ₂ mixed at 14.8 ppg. cemented with 200 sacks to surface. 2 hours. |
| SHOOT OR ACIDIZE REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLET proposed work. If well is nent to this work.)* 4-3-86 - Set 3200 Cemented Followed Did not Chass C n 30 minute I bereby certify that the foreg SIGNED | CHANGE PLANE FED OPERATIONS (Clearly state all I directionally drilled, give subsurfa feet of 9-5/8" K-55 with 450 sacks HL w, with 400 sacks Class circulated. Ran 630 nixed at 14.8 ppg. (C ES pressure tested to ACCEPTED FOR ACCEPTED FOR ADR 14 19 CARISBAD, NEW | (Other) Casing (Nors: Report Completion or Pertinent details, and give pertiner ice locations and measured and tru L-80 40#. /½# Flocele & 2% CaCl s C w/½# Flocele & 2% feet of 1" pipe and Circulated 25 sacks t D 2000#. WOC - 24-1/ RECORD | 2 test & cement job t results of multiple completion on Well Recompletion Report and Log form.) and dates, including estimated date of starting any revertical depths for all markers and gones perti- 2 mixed at 12.7 ppg. CaCl ₂ mixed at 14.8 ppg. cemented with 200 sacks to surface. 2 hours. |
| SHOOT OR ACIDIZE REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLET proposed work. If well is nent to this work.)* 4-3-86 - Set 3200 Cemented Followed Did not Chass C n 30 minute 1 hereby certify that the toreg SIGNED | CHANGE PLANE TED OPERATIONS (Clearly state all p directionally drilled, give subsurfa feet of 9-5/8" K-55 with 450 sacks HL w, with 400 sacks Class circulated. Ran 630 mixed at 14.8 ppg. (C es pressure tested to ACCEPTED FOR ADD APR 14 19 CAPISBAD, NEW oling is true and correct Detty Gildon te office use) TITLE | (Other) Casing (Norr: Report Completion or Pertiment details, and give pertimer ice locations and measured and tru L-80 40#. /½# Flocele & 2% CaCl s C w/½# Flocele & 2% feet of 1" pipe and Circulated 25 sacks t to 2000#. WOC - 24-1/ RECORD | 2 test & cement job t results of multiple completion on Well Recompletion Report and Log form.) and dates, including estimated date of starting any revertical depths for all markers and gones perti- 2 mixed at 12.7 ppg. CaCl ₂ mixed at 14.8 ppg. cemented with 200 sacks to surface. 2 hours. |

-÷ -___

Title 18 U.S.C. Section 1001, makes it a crime tor any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.