

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Pogo Producing Company

3. ADDRESS OF OPERATOR

P.O. Box 10340 Midland, Tx. 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FSL & 660' FEL

AT TOP PROD. INTERVAL: 660' FSL & 660' FEL

AT TOTAL DEPTH: 660' FSL & 660' FEL

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☒

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5/8/86 MW 10#, Vis 29

3 1/2 Hrs. LD DC, RIH OE to 6008'

1 1/2 Hrs. Circ & WO Cementer

1/4 Hr. DP @ 6008', spot 45 sxs C1 C neat

1 1/4 Hrs. POH to 4373', spot 35 sxs C1 C neat

1 1/4 Hrs. POH to 2200', spot 40 sxs C1 C neat

1 1/4 Hrs. POH to 608', spot 40 sxs C1 C + 3% CaCl₂

3 1/2 Hrs. WOC

5/9/86 MW 10#, Vis 29

1/2 Hr. RIH, TOL @ 688'

3 1/2 Hrs. WOC

1/4 Hr. DP @ 608', spot 40 sxs C1 C + 3% CaCl₂

CONTINUED ON ATTACHED SHEET

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Petroleum Engineer

DATE

6/2/86

Orig. Sgd. Linda S. C. Rundle

(This space for Federal or State office use)

APPROVED BY Acting Area Manager

TITLE

DATE

2-12-87

CONDITIONS OF APPROVAL, IF ANY:

Approved as to...
Liability...
surface...
...

