

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
well well

2. NAME OF OPERATOR

Pogo Producing Company

3. ADDRESS OF OPERATOR

P. O. Box 10340, Midland, TX. 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FN & EL

AT TOP PROD. INTERVAL: 1980' FN & EL

AT TOTAL DEPTH: 1980' FN & EL

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Spud well & run surface casing

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

7/23/86 MIRU Peterson Drilling Company rig #2.  
Spud well @ 11:00pm MDT 7/23/86.

7/24/86 TD 554'. MW 8.8#

Ran 15 jts 543.04' 8-5/8" 24# K-55 ST&C Rg 3 csg, FS 1.0' + 11' landing joint. (Total string 555.04'). FS + 1 jt + IF + 1 jt thrd lkd. Cent on 1,3,5,7 & 9th jts.

FS @ 554'. Howco cmtd w/350 sxs Cl C + 1/4# flocele per sx + 2% CaCl<sub>2</sub> (14.8 ppg). Circ 63 sxs. CIP @ 5:00pm MDT 7/24/86.

Witnessed by Joe Marabel w/BLM.

12 hrs WOC, cutoff 8-5/8" & NU BOP.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

David Beathard

TITLE Petroleum Engineer

DATE 8/11/86

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

AUG 19 1986

\*See Instructions on Reverse Side