

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT


NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.G.S.	
LAND OFFICE	
OPERATOR	☒

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78



5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REWORK OR RE-ENTER TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT ** (FOR ARTESIAN OR SUCH PURPOSES).)

1. OIL WELL ☐ GAS WELL ☒ OTHER- 30-015-25708	7. Unit Agreement Name
Name of Operator Pogo Producing Company	8. Farm or Lease Name IMC
Address of Operator P. O. Box 10340, Midland, Texas 79702	9. Well No. 1
4. Location of Well UNIT LETTER C 660 FEET FROM THE North LINE AND 1650 FEET FROM THE West LINE, SECTION 26 TOWNSHIP 24-S RANGE 28-E	10. Field and Pool, or adjacent Malaga (Morrow)
15. Elevation (Show whether DF, RT, GR, etc.) 2959.2 GR, 2986' KB	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2/27/87-Spot cmt plug 12,328'-12,228', 45 sxs C1 H + 0.5% TF-4. Spot cmt plug 11,854'-11,754', 80 sxs C1 H + 0.5% TF-4. Spot cmt plug 11,272'-11,172', 50 sxs C1 H + 0.5% TF-4. POH DP. Rig McCullough, RIH CIBP on WL, set @ 9850'. RIH DP OE, tagged plug @ 9850'.

2/28/87-Circ off gas. Take SI DP pressure, 0#. Spot cmt plug @ top of CIBP, 9850'-9776', 25 sxs C1 H + 0.5% TF-4. Spot cmt plug 9555'-9455', 40 sxs C1 H + 0.5% TF-4. Spot cmt plug 9194'-9094', 42 sxs C1 H + 0.5% TF-4. Spot cmt plug 8132'-8032', 42 sxs C1 H + 0.5% TF-4. Spot cmt plug 6100'-6000', 35 sxs C1 C. Spot cmt plug @ DV tool, 5249'-5149', 35 sxs C1 C. Spot cmt plug 3700'-3600', 35 sxs C1 C. POH LD 120 jts DP + 21 DC. McCullough perforated 9 5/8" csg w/ 4 shots @ 2697'. RIH DP to 2697', break circ through 9 5/8"-13 3/8" annulus. Cmt annulus w/65 sxs C1 C & spot 35 sxs C1 C in 9 5/8" csg 2697'-2597'. LD 84 jts DP. Perf 9 5/8" csg @ 676' w/4 shots. RIH DP to 576'. Cmt annulus w/35 sxs C1 C & spot 35 sxs C1 C in 9 5/8" csg.

3/1/87-ND BOE, cut off WH. Spot 25 sxs C1 C @ surface. Weld on dry hole marker. Clean pits.

Post ID-2
3-27-87
P+A

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

David Beathard

SIGNED David Beathard TITLE Petroleum Engineer DATE 3/4/87

APPROVED BY Danell Moore TITLE Geologist DATE 9/15/88

CONDITIONS OF APPROVAL, IF ANY: