

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE
(Other instructions on reverse side)

Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Phillips Petroleum Company

3. ADDRESS OF OPERATOR

4001 Penbrook Street, Odessa, Texas 79762

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

Unit C, 535' FNL & 2080' FWL

14. PERMIT NO.

API No. 30-015-25756

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3176.5' GR

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANE

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Spud and set casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

6-02-87: Spud 17-1/2" hole at 2:05 P.M. MST. Td-d 17-1/2" hole at 11:45 P.M.
Lost circulation at 245', mixed LCM pill. Set 13-3/8" 54.5# K-55
ST&C casing at 418'. Cmt'd with 650 sx Class "C", 2% CaCl₂. Circ 25 sx
to surface.

6-03 thru

6-08-87: WOC 24 hrs. NU BOP. Tested BOP to 600 psi. TD'd 12-1/4" hole at
3500' on 6-07-87. Set 8-5/8" 32# & 24# K-55 ST&C casing at 3500'.
Cmt'd with 950 sx Class "C", 20% Diacel D, 23#/sx salt, 1/2#/sx
celloseal plus 200 sx Class "C" with 10#/sx salt. Displaced 215 BFW. Casing reciprocated 20'. Circulated 200 sx to surface.
Total WOC time 24 hrs. Tested BOP to 1000 psi, held ok.

6-09

thru

6-12-87 Drlg. 5444' PTD.

ACCEPTED FOR RECORD

JUN 17 1987

SJS
CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED W. J. Mueller TITLE Engineering Supervisor DATE June 12, 1987

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side