Submit 3 Copies to Appropriate

## State of New Mexico



MAY 1 4 1993

Form C-103 Energy, Minerals and Natural Resources Department Revised 1-1-89 District Office OIL CONSERVATION DIVISION WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 RECEIVED Santa Fe, New Mexico 87504-2088 P.O. Box 2088 30-015-25758 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 5. Indicate Type of Lease APR 29 1993 STATE X FEE DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. K-3271 C. L. D. SUNDRY NOTICES AND REPORTS ON WELLS ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: James A WELL 2. Name of Operator Phillips Petroleum Company 3. Address of Operator 9. Pool name or Wildcat 4001 Penbrook Street, Odessa, TX, 79762 Cabin Lake (Delaware) 4. Well Location Line and 1980 1980 Feet From The South West Unit Letter \_ Feet From The Line 2 22-S 30-E Eddy Township **NMPM** County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3178.6'DF; 3167.6'GL Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK **ALTERING CASING** TEMPORARILY ABANDON **CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT **PULL OR ALTER CASING** CASING TEST AND CEMENT JOB OTHER: Convert to SWD OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 4-2-93 - Installed BOP. WIH w/5-1/2" Baker Lok-set pkr. on 2-7/8" tubing to 4600'. Displaced hole with packer fluid (Treatolite KW-170. Set pkr. Pressured tubing-casing annulus to 500 psi. Would not hold. Unseat pkr. and POH. 4-3-93 - Picked up re-dressed 5-1/2" Baker Lok-set, internally plastic coated. Tested tubing to 5,000 psi while going in hole. WIH to 4600'. Displaced hole with packer fluid. Set packer at 4600'. Pressure tested tubingcasing annulus to 500 psi for 20 min. Test o.k. Removed BOP. NMOCD was notified to witness test. Gave approval to test and send them a chart of the test. Well Shut In pending installation of the 2-1/2" high pressure injection line. 5-21-93 che from Prod to SWD plets to the best of my knowledge and belief. Supv.Regulatory Affairs DATE 04-27-93 (915) TRIZETHONE NO. 368-1488 L. M. Sanders TYPE OR PRINT NAME (This space for State Use) ORIGINAL: SIGNED BY

SUPERVISOR, DISTRICT IT APPROVED BY ... CONDITIONS OF AFTROVAL, IF ANY:

MIKE WILLIAMS