

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.B.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-76

OCT 15 '87

O. C. D.

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

ARTESIA, OFFICE

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL OTHER	7. Unit Agreement Name
2. Name of Operator Western Oil Producers, Inc.	8. Farm or Lease Name Bass
3. Address of Operator P.O. Box 1498 Roswell, New Mexico 88201	9. Well No. 2
4. Location of Well UNIT LETTER L 1980 FEET FROM THE South LINE AND 660' FEET FROM THE West LINE, SECTION 1 TOWNSHIP 22S RANGE 27E NMPM.	10. Field and Pool, or Whichever UNL E 1/4 SEC 16 T22S R27E
15. Elevation (Show whether DF, RT, GR, etc.) 3088.6	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
FULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9/28/87 Spud 17 1/2" hole 8:30 PM

9/30/87 Drilling, Depth 470', Formation lime, 90' of progress, drilling with water, Deviation 387' - 1/2°, Bit wt. all, RPM 70, Bit #1 10 hrs., 347' came out at 387', Bit #2 1 1/4 hrs., 83', still drilling, ran 11 jts. 405' 13 3/8" 61 lb. casing, cemented at 387' with 400 sx. Class C 2% Calcium Chloride, 1/4 lb. flocele, cement circulated to bottom of cellar then fell back, filled back side with ready mix, Plug down 12:45 PM 9/29/87.

10/4/87 Drilling, depth 2370', formation lime and sand, 170' of progress, drilling with water, deviation 2,000' - 2°, Bit #4 5 hrs., 170', still drilling, Ran 51 jts., 2215', 8 5/8" 24 and 32 lb. casing, cemented at 220' with 725 sx. Halliburton lite, 15 lbs. salt, 14/ lb. folcele, 250 sx Class C 2% Calcium Chloride, circulate 35 sx., plug down 1:15 PM 10/3/87. Differential pressure 600 lbs. pressure plugged to 1500 holding ok.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Arnold Hewit TITLE Agent DATE 10/14/87

Original Signed By
Les A. Clements

OCT 20 1987

APPROVED BY Supervisor District II TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: