

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NEW OIL DRILL
Artesia, NM

DATE
01/10

Form approved
Budget Bureau No. 1004-4-1
Expires August 31, 1985

458

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

D. L. COOK

3. ADDRESS OF OPERATOR

4017 Travis Street, Dallas, TX. 75204

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below)
At surface

990' FNL, 1980' FEL (NWNE)

14. PERMIT NO.

15. ELEVATIONS (Show whether DEL, GR, etc.)

3883' GR.

3886' KB

16

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO

TEST WATER SHUT-OFF

FRAC TURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

OTHER

PULL OR ALTER Casing

MULTIPLE COMPLETION

ABANDON

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRAC TURE TREATMENT

SHOOTING OR ACIDIZING

OTHER

REPAIRING WELL

ALTERING CASING

ABANDONMENT

Current Operations Status

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATION (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Drilled to a depth of 2020'. No returns after 1225'. Estimated base of the Capitan Reef 1986'.

3-4-88 Ran 1996' of 4½" STC J-55 10.50# casing. Haliburton cemented with 275 sks. Hal Light, ½# Flocele, tailed with 100 sks. Premium, ¼# Flowcele, 2% CalChlor. - No circulation.

3-5-88 Ran temperature Survey - Top of cement at 1300'.
1st. plug staged with 3/4" tubing @ 1111', 30 sks. Prem. Plus, 3% CalChlor. No Circulation.

2nd. plug (no tag) @ 1111', w/35 sks. Prem. Plus, 3% CalChlor. No Circ.

3rd. plug (no tag) @ 1111', w/35 sks. Prem. Plus, 3% CalChlor. No Circ.

3-6-88 4th. plug Tagged cement @ 929', staged w/35 sks. Prem. Plus, 3% CalChlor. No circulation.

5th. plug Tagged cement @ 729', staged w/35 sks. Prem. Plus, 3% CalChlor. No circulation.

6th. plug-Tagged cement @ 470', staged w/60 sks. Prem. Plus Neet, 2% CalChlor. and circulated to surface.

Released rig, will move back over hole and drill out cement and continue operations within the next thirty (30) days.

18. I hereby certify that the foregoing is true and correct.

SIGNED

TITLE Agent

DATE 3-9-88

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

SJS