Subm. 3 Copies to Appropriate District Office

11.

OTHER:

PERFORM REMEDIAL WORK

TEMPORARILY ABANDON

PULL OR ALTER CASING

State of New Mexico 3y, Minerals and Natural Resources Departr

Form C-103
Revised 1-1-4

FEE

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

I CLEIVED DOT'1 1 1993 30-015-25866

WELL API NO.

5. Indicate Type of Lease STATEXX

6. State Oil & Gas Lease No.

Feet From The

(M-7-1-1000)	V-3589
SUNDRY NOTICES AND REPORTS ON WELLS C. D. (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	7. Lease Name or Unit Agreement Name
. Type of Well: Oil. GAS WELL X WELL OTHER	Pauline ALB State
Name of Operator YATES PETROLEUM CORPORATION	8. Well No. 6
. Address of Operator 105 South Fourth Street - Artesia, NM 88210	9. Pool name of Wildcat Ingle Wells Bone Springs/ W. Sand Dunes Delaware
Well Location	

Eddy County **NMPM** Range Section Township 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3370.5' GR

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO:

South

PLUG AND ABANDON

REMEDIAL WORK COMMENCE DRILLING OPNS

Line and

ALTERING CASING PLUG AND ABANDONMENT

CHANGE PLANS

: 1980 Feet From The _

CASING TEST AND CEMENT JOB

Frac perforations OTHER:_

1980

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moved in and rigged up pulling unit. Unseat pump. TOOH with rods. Released tubing anchor catcher. Strip on BOP. TOOH with tubing. TIH w/7" 29# packer and RBP. Set RBP at 7970'. Tested to 2000#. Set packer at 7600'. Loaded annulus with KCL water. Would not load. Frac'd perforations 7702-7936' (Delaware) (via tubing) with 10000 gallons linear gel, 57500 gallons crosslink gel, 115000# 20-40 Brady sand and 60000# 16-30 resin coated sand. Released packer & TOOH. Cleaned out sand to 7970'. POOH. TIH w/production tubing. Strip off BOP. Set tubing anchor catcher at 5900' and seating nipple at 7550'. Nippled up tubing head. TIH w/rods and pump. Hung well on. Returned to production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. DATE Oct. 8, 1993 Production Clerk SIGNATURE 2 505-748-1471 TELEPHONE NO. TYPEORPRINT NAME Rusty Klein (This space for State Use) ORIGINAL: SIGNED BY

MIKE WILLIAMS

SUPERVISOR DISTRICT I

OCT 1 9 1993

APPROVED BY