

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P. O. Box 1980, Hobbs, NM 88240

DISTRICT II
P. O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P. O. Box 2088
Santa Fe, New Mexico 87504-2088

JAN 10 '89

WELL API NO. 30-015-26031
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. K-3271
7. Lease Name or Unit Agreement Name James A
8. Well No. 6
9. Pool name or Wildcat Cabin Lake (Delaware)

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator Phillips Petroleum Company
3. Address of Operator 4001 Penbrook St., Odessa, TX 79762	4. Well Location Unit Letter I : 1980 Feet From The South Line and 660 Feet From The East Line Section 2 Township 22S Range 30E NMPM
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3215	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12/17/88 MI & RU. Spud 17-1/2" hole.

12/18/88 Ran 9 jts. 13-3/8" 48#, H-40, ST&C casing and set @ 410'. Cmt'd. w/700 sacks Class C 2% CaCl. Did not circulate. Pump 25 sacks Class C 4% CaCl and cemented to surface. WOC 20 hrs. Drilling 12-1/4" hole. Tested casing to 600 psi for 30 min - OK.

12/23/88 Ran 8-5/8" 24# K-55 ST&C csg. and set @ 3488'. Cmt'd. w/1000 sack Class C 2% Diace1 D and 200 sacks Class C 2% CaCl. Circ. 210 sack to surface. WOC 18+ hrs. Tested casing to 1000 psi for 30 min.

12/26/88 Drilling 7-7/8" hole.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE W. J. Mueller

TITLE Eng. Supervisor, Res.

DATE 12/29/88

TYPE OR PRINT NAME

TELEPHONE NO. (Sanders) 915-367-1488

(This space for State Use)

Original Signed By
Mike Williams

APPROVED BY

TITLE

DATE

JAN 10 1989

CONDITIONS OF APPROVAL, IF ANY: