State of New Mexico

C171 Revised 1-1-29

Energy, Minerals and Natural Resources Department to Appropriate District Office RECEIVED OIL CONSERVATION DIVISION **DISTRICT I** WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-015-26036 JAN 125anca Fe; New Mexico 87504-2088 DISTRICT I P.O. Drawer DD, Artesia, NM 88210 5. Indicate Type of Lease FEE X STATE 6. State Oil & Gas Lease No. O. C. D. 1000 Rio Brazos Rd., Aztec, NM 87410 ARTESIA, OFFICE SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Pardue Farms 27 1. Type of Well: GAS WELL WELL X 075-888 2. Name of Operator 8. Well No. Parker & Parsley Petroleum Company 9. Pool name or Wildcat South Culebra Bluff 3. Address of Operator P. O. Box 3178, Midland, Texas (Bone Spring) Well Location 560 North East 560 Feet From The Feet From The Line Unit Letter __ 28-E Eddy thip 23-S Range 28-E

10. Elevation (Show whether DF, RKB, RT, GR, etc.) 23-S **NMPM** Township County 3036.1 GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PERFORM REMEDIAL WORK TEMPORARILY ABANDON **CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB X **PULL OR ALTER CASING** OTHER:_ OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 1-1-89 Reach TD @7508'. 1-2-89 Ran 197 its. 5 1/2" csg. as follows: 178 jts. 15.5# - 6786**'** 19 its. 17.0# - 722' 75081 Set @7508'. Used DF float shoe, DF float collar, 43 turbolizers, 2 cmt. baskets. Set DV tool @5002', 3 5/8" BR @6799' & 3 3/8" BR @7169'. Cmt. 1st stage w/350 sx. Self Stress (Class "H" + 10% D-53 + 10% salt). Opened DV tool & circ. 5 1/2 hrs. w/mud. Cmt. 2nd stage w/550 sx Self Stress (Class "H" + 10% D-53 +10% salt). Closed DV tool, set slips, cut off. WOC 18 hrs. Test csg. to 600 psig f/30 minutes, OK. Ran Bond Log, top of cmt. @3560'.

I hereby certify that the information at SIGNATURE	boyse is true and complete to the best of my knowledge and belief.	Operations Engineer	DATE
(This space for State Use)	Original Signed By		JAN 1 1 110

TITLE .

APPROVED BY-

SIVED

JEN 11 1989 OCD HOBBS OFFICE