

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

NOV 1 - '89

WELL API NO.	30 015 26111
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	7. Lease Name or Unit Agreement Name Willow Lake 15
2. Name of Operator Enron Oil & Gas Company	8. Well No. 1
3. Address of Operator P. O. Box 2267, Midland, Texas 79702	9. Pool name or Wildcat Willow Lake
4. Well Location Unit Letter 0 : 660 Feet From The south Line and 1980 Feet From The east Line Section 15 Township 24S Range 28E NMPM Eddy County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3002.8' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF: 9/15/89
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-13-89 - Set 7" est @ 10,476'. 26# P110.

Cemented with 350 sx of C1 "H" 35/65 poz + 6% D-20 + .3 of one percent D-112, yield 2.23 cuft/sx, 12.1 ppg and 300 sx of C1 "H" + .4 of one percent D-133, yield 1.18 cuft/sx, 15.6 ppg. 1/2 hr press tested to 3000# OK. WOC - 27-3/4 hr.

9-25-89 - Set 4-1/2" liner at 11,828'. TOL @ 10,184. (4-1/2" 15.10# P110 FL-4S)

Cemented with 30 bbls of spacer fluid mixed at 13.5 ppg w/D-13 & 294 sx of C1 "H" + 2gas/sx D-600 + .05 gal/sx M-45 + .1 of one percent D-13 + .2 of one percent D-65, yield 1.09 cuft/sx, 16.2 ppg. 1/2 hr press tested to 2500# OK. WOC - 18 hours.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Betty Gildon TITLE Regulatory Analyst DATE 10/27/89
TYPE OR PRINT NAME Betty Gildon TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY
DATE
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE NOV 6 1989

CONDITIONS OF APPROVAL, IF ANY: