

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME Lotos "A" Federal Com
2. NAME OF OPERATOR Bettis, Boyle & Stovall	8. FARM OR LEASE NAME Lotos "A"
3. ADDRESS OF OPERATOR P. O. Box 1240 Graham, Texas 76046 C. D.	9. WELL NO. -1-
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FNL & 1980' FWL of Sec. 15-T24S-R31E	10. FIELD AND POOL, OR WILDCAT Wildcat
14. PERMIT NO. Case#9692, Od R-8974	11. SEC., T., R., E., OR BLK. AND SURVEY OR AREA Sec. 15-T24S-R31-E
15. ELEVATIONS (Show whether DF, RT, OR, etc.) 3501.6 GL	12. COUNTY OR PARISH Eddy
	13. STATE NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	PULL OR ALTER CASING
FRACTURE TREAT	MULTIPLE COMPLETE
SHOOT OR ACIDIZE	ABANDON*
REPAIR WELL	CHANGE PLANS
(Other)	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREATMENT	ALTERING CASING
SHOOTING OR ACIDIZING	ABANDONMENT*
(Other) Casing Detail	X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

9/9/89 - Set 20', 94# K55 @ 671' cemented w/725 sx Halliburton Lite 2% CC, 1/4# flowcel & 500 sx class C 2% cc, circ. 200 sx to reserve.

9/17/89 - Set 13-3/8" 72# N80, at 4400', cemented with 2800 sx Halliburton Lite 12# salt, 1/4 floseal, 2% cc, + 500 sx Calss C neat, circulated 200 sx to reserve.

10/10/89 - Set 9-5/8", 53.5, 47 & 43.5# at 11,750', cemented with 400 sx 50/50 poz mix prem. w/2% gel, 8/10% halad.

11/25/89 - Set 7", 35#, C-95 & L-80 liner from 11,490' to 16,426' with 475 sx Class H, squeezed top fo lienr w/200 sx Class H

ACCEPTED FOR RECORD

MAY 24 1990

18. I hereby certify that the foregoing is true and correct

CARLSBAD, NEW MEXICO

SIGNED

TITLE Production Assistant

DATE 2/12/90

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side