

RECEIVED

JUL 13 10 47 AM '94

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-40659

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Sand Dunes 28 Fed. #1 SWD

9. API Well No.

30-015-21194

10. Field and Pool, or Exploratory Area

Sand Dunes

11. County or Parish, State

Eddy County, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other

SWD

2. Name of Operator

Pogo Producing Company

3. Address and Telephone No.

P. O. Box 10340, Midland, TX 79702-7340 (915)682-6822

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 1980' FEL, Section 28, T23S, R31E

AUG 03 '94

O. C. D.
ARTESIA, OFFICE

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment☒ Recompletion☒ Plugging Back☐ Casing Repair☐ Altering Casing☒ Other

Re-Entry

☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

3/17-3/21/94 Drilled out cement plugs @ 50', 711', 3685', 4295' & 5044'.
3/21-3/23/94 Dress-off 7" casing.
3/26/94 Run 7" casing & tie into top of existing 7" casing @ 4846'.
3/27/94 Perf 7" casing w/ 4 squeeze holes @ 6100'. Set circ @ 5979' & cement squeeze holes w/ 200 sx Class "H" cement.
3/29/94 Perf 7" casing w/ 4 squeeze holes @ 4800'. Set circ @ 4753' & cement squeeze holes w/ 660 sx Class "C" + 3 pps Gilsonite + 2.8 pps KCl + .8% H-322 + .3% H-344.
3/30/94 Perf 7" casing w/ 4 squeeze holes @ 1450'. Set circ @ 1395' & cement w/ 140 sx Halliburton Lite followed by 50 sx Class "C". Recovered 35 sx excess cement.

14. I hereby certify that the foregoing is true and correct

Signed

Title Senior Operations Engineer

Date July 12, 1994

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

SJS

1994

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side