

## PROPOSED DRILLING FLUID PROGRAM

### 0 - 450'±

Spud mud consisting of AQUAGEL flocculated with Lime. Use ground paper for seepage loss of fluid and KWIK-SEAL, FIBERTEX and Cottonseed Hulls for severe or total loss.

If total loss of circulation occurs, we suggest mixing two or three 150-200 barrel pills of viscous AQUAGEL/Lime mud treated with 10-15 ppb KWIK-SEAL and/or Cottonseed Hulls. If this does not regain circulation, we suggest drilling to casing point without returns and spotting a similar pill on bottom prior to logging and running casing.

### 450 - 2700'±

Drill out with brine water and treat with CON DET and BEN-EX/MF-1 to flocculate solids. Circulate controlled section of the reserve pit. Use ground paper for seepage loss. Use pre-hydrated AQUAGEL or ZEOGEL/paper slugs as needed to sweep hole. For corrosion control, use Sodium Bichromate.

### 2700 - 10600'

Drill out with fresh water or cut brine circulating a controlled section of the reserve pit using BEN-EX/MF-1 and CON DET for control of solids build up. The fluid weight in this interval should be 8.5 - 9.5 ppg. Use ZEOGEL/ground paper or pre-hydrated AQUAGEL pills to sweep the hole free of cuttings when needed and prior to trips. Use Lime for a 9.0 - 9.5 pH. Use Sodium Bichromate at 600 - 800 ppm concentration for drill pipe and casing corrosion control.

The additions of MR-1/BEN-EX and CON DET may be used for control of solids build up. Use ZEOGEL/ground paper sweeps for seepage and additional hole cleaning. Should abnormal pressures be encountered, an early mud up may be necessary.

### 10600 - 12250'

Prior to entering the Atoka, limit circulation to the steel pits and treat out hardness with Soda Ash. Lower filtrate to 10-15 cc with DEXTRID/PAC-R. Add XP Polymer for desired viscosity. Use BAROID for density as dictated by hole conditions. This non-dispersed bipolymer system should have the following properties:

Weight:	To be dictated by hole conditions
Viscosity:	34-38 sec/1000 cc
Filter Loss:	10-15 ml

Exhibit C  
Santa Fe Energy Oper. Part., LP  
Malaga 1 Fed Com No. 1  
Sec. 1, T-24S, R-28E  
Eddy County, New Mexico