

## SUPPLEMENTAL DRILLING DATA

### NEARBURG PRODUCING COMPANY

#### BANDANA POINT 10C FEDERAL WELL NO. 1

##### 1. SURFACE FORMATION:

Dockum Group of Triassic Age.

##### 2. ESTIMATED TOPS OF GEOLOGIC MARKERS:

Glorieta.....1,950'  
Abo.....3,970'  
Wolfcamp.....6,750'  
Cisco.....7,650'  
Canyon.....7,920'  
Strawn.....8,500'  
Atoka.....8,870'  
Morrow.....9,400'  
Barnett.....9,900'

##### 3. ANTICIPATED POSSIBLE HYDROCARBON BEARING ZONES:

Morrow

##### 4. CASING AND CEMENTING PROGRAM:

<u>Casing Size</u>	<u>Setting Depth</u>		<u>Weight</u>	<u>Grade</u>	<u>Joint</u>
	<u>From</u>	<u>To</u>			
13-3/8"	0'	350'	48#	J-55	ST&C
8-5/8"	0'	2,400'	24#	J-55	ST&C
4-1/2"	0'	10,000'	11.6#	J & N	LT&C

Equivalent or adequate grades and weights of casing may be substituted at time casing is run, depending on availability.

13-3/8" casing will be cemented with 400 sx or volume necessary to circulate.

8-5/8" casing will be cemented with 1,000 sx or volume necessary to tie back into 13-3/8".

4-1/2" production casing will be cemented with approximately 850 sx of Class "H" 50/50 POZ. 525