

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT --" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well: ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator
TEXACO EXPLORATION & PRODUCTION INC.

3. Address and Telephone No. P.O. BOX 730, HOBBS, NM 88240 397-0418

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit Letter B : 660 Feet From The NORTH Line and 2310 Feet From The

EAST Line Section 24 Township 22S Range 31E

5. Lease Designation and Serial No.

NM-29299

6. If Indian, Alottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and Number

GETTY 24 FEDERAL

3

9. API Well No.

30-015-26288

10. Field and Pool, Exploratory Area

LIVINGSTON RIDGE DELAWARE

11. County or Parish, State

EDDY, NEW MEXICO

12. Check Appropriate Box(s) To Indicate Nature of Notice, Report, or Other Data

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ OTHER: ADDED PAY & STIMULATED
- ☐ Change of Plans
☒ New Construction
☒ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

RECEIVED

APR 01 1996

OIL CON. DIV.

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- (11/27/95 - 1/4/96) 1. MIRU PULLING UNIT. TOH W/ RODS & PUMP. INSTALLED BOP. RELEASED TAC. TOH W/ TBG.
2. SET 5 1/2" RBP @ 7800'. TST RBP & CSG TO 2000#, OK. DMPD 10' SND ON TOP RBP. RAN GR-CCL LOG FR 7800'-5800' (DV TL @ 5991').
3. PERFORATED THE FOLLOWING INTERVAL W/ 2 JSPF: 7054' - 7080' (26' NET, 52 HOLES) W/ 4" CSG GUN W/ 120 DEG PHASING.
4. TIH W/ 5 1/2" TREATING PKR & SN ON 3 1/2" TBG. TSTD TBG INTO HOLE TO 6000#. SET PKR @ 6953'. ND BOP, NU 5000# FRAC TREE. LOADED BACKSIDE & TEST PKR TO 1000#, OK. RU FLOWBACK LINES OFF ADJUSTABLE CHOKE TO PIT.
5. ACIDIZED BRUSHY CANYON PERFS 7054'-7080' W/ 1500 GALS 7 1/2% NEFE HCL W/ BALLSEALERS. MAX P = 2950#, AIR = 7 BPM.
6. SI 1 HOUR. ND TREE, NU BOP. RELEASED PKR, RAN THROUGH PERFS TO KNOCK OFF BALL SEALERS. RESET PKR @ 6953'. ND BOP, NU FRAC TREE. LOADED BACKSIDE & TSTD PKR TO 1000#, OK.
7. FRACTURE TREATED BRUSHY CANYON PERFS 7054'-7080' W/ 11,500 GALLONS 30# BORATE XLG 2% KCL CARRYING 65,000# 20/40 OTTOWA SAND. MAX P = 4800#, AIR = 20 BPM. PLACED 500# ON BS & MONITORED DURING JOB.
8. SWABBED BACK WELL. ND FRAC TREE, NU BOP. RELEASED & TOH W/ PKR. TIH W/ 5 1/2" RBP & SET ABOVE PERFS @ 7030'. TSTD RBP TO 2000#. DUMPED 10' SND ON TOP OF RBP.
9. PERFORATED FOLLOWING INT W/ 2 JSPF: 6958' - 6982' (24' NET, 48 HOLES) W/ 4" CSG GUN W/ 120 DEG PHASING.
10. TIH W/ 5 1/2" TREATING PKR ON 3 1/2" TBG. SET PKR @ 6855'. ND BOP, NU 5000# FRAC TREE. LOAD BS & TSTD PKR TO 1000#, OK.
11. ACIDIZED BRUSHY CANYON PERFS 6958'-6982' W/ 1500 GALLONS 7 1/2% NEFE HCL W/ BALLSEALERS. MAX P = 1700#, AIR = 7 BPM.
12. ND TREE, NU BOP. REL PKR, RUN THRU PERFS TO KNOCK OFF BS. RESET PKR @ 6855'. SWABBED BACK. ND BOP, NU FRAC TREE. LOADED BACKSIDE & TSTD PKR TO 1000#, OK. FRACD BRUSHY CANYON PERFS 6958'-6982' W/ 11,500 GALLONS 30# BORATE XLG 2% KCL CARRYING 65,000# 20/40 OTTOWA SAND. MAX P = 4900#, AIR = 20 BPM. PLACED 500# ON BS & MONITORED DURING JOB.
13. SWABBED BACK WELL. ND FRAC TREE, NU BOP. RELEASED & TOH W/ PKR. TAGGED SAND @ 6990', C/O TO RBP @ 7030'. TIH W/ RETRIEVING TOOL, TOOL GOT STUCK IN SAND @ 7032'. BACKED OFF TOOL @ 7032', USED FOAM UNIT TO C/O TO RETRIEVING TOOL & RBP. FISHED OUT TOOL & RBP. C/O SAND TO RBP @ 7800', RELEASED & TOH W/ RBP. C/O HOLE TO PBTD @ 8385'.
14. TIH W/ PROD EQUIP & RETD TO PROD. OPT 2/4/96 BY ROD PUMP: 89 BOPD, 45 BWPD, 60 MCFD (TEPI STATUS REMAINS PM)

14. I hereby certify that the foregoing is true and correct

SIGNATURE Monte C. Duncan TITLE Engr Asst DATE 2/7/96

TYPE OR PRINT NAME Monte C. Duncan

(This space for Federal or State office use)

APPROVED BY J. L. [Signature] TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.